



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :
H04L 12/00

A2

(11) International Publication Number: WO 00/51290

(43) International Publication Date: 31 August 2000 (31.08.00)

(21) International Application Number: PCT/US00/04717

(22) International Filing Date: 23 February 2000 (23.02.00)

(30) Priority Data:

60/121,270	23 February 1999 (23.02.99)	US
60/121,271	23 February 1999 (23.02.99)	US
60/121,272	23 February 1999 (23.02.99)	US
60/121,273	23 February 1999 (23.02.99)	US
60/121,274	23 February 1999 (23.02.99)	US
60/121,275	23 February 1999 (23.02.99)	US
60/121,276	23 February 1999 (23.02.99)	US
60/121,277	23 February 1999 (23.02.99)	US
60/121,278	23 February 1999 (23.02.99)	US
60/121,279	23 February 1999 (23.02.99)	US
60/121,589	23 February 1999 (23.02.99)	US
60/121,590	23 February 1999 (23.02.99)	US
60/121,591	23 February 1999 (23.02.99)	US
60/121,592	23 February 1999 (23.02.99)	US
60/121,593	23 February 1999 (23.02.99)	US

(71) Applicant: ALCATEL INTERNETWORKING, INC.
[US/US]; 26801 West Agoura Road, Calabasas, CA 91301 (US).

(72) Inventors: RAO, Ramakrishna; 916 Pramukh's Way, San Jose, CA 95120 (US). GHAREMANI, Charlie; 6566 Deer Hollow Drive, San Jose, CA 95120 (US). YOUNG, Desmond; 23050 Old Logging Road, Los Gatos Mountains, CA 95033 (US). MURTHY, Manohar; 1969 Vinehill Circle, Fremont, CA 94539 (US). TSENG, Ben; 4121 Wilkie Court, Palo Alto, CA 94306 (US). NAGARAJ, Ashwath; 25769 Elena Road, Los Altos, CA 94022 (US). FARID, Mehdi; 22540 Hutchinson Road, Los Gatos, CA 95033 (US). SCHUNK, Richard; 64 King Street, Norfolk, MA 02056 (US).


(74) Agent: CHANG, Josephine, E.; Christie, Parker & Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).

(81) Designated States: AU, CN, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: MULTI-SERVICE NETWORK SWITCH



(57) Abstract

A multi-service network switch capable of providing multiple network services from a single platform. The switch incorporates a distributed packet forwarding architecture where each of the various cards is capable of making independent forwarding decisions. The switch further allows for dynamic resource management for dynamically assigning modem and ISDN resources to an incoming call. The switch may also include fault management features to guard against single points of failure within the switch. The switch further allows the partitioning of the switch into multiple virtual routers where each virtual router has its own set of resources and a routing table. Each virtual router is further partitioned into virtual private networks for further controlling access to the network. The switch's supports policy based routing where specific routing paths are selected based a domain name, a telephone number, and the like. The switch also provides tiered access of the Internet by defining quality of access levels to each incoming connection request. The switch may further support an IP routing protocol and architecture in which the layer two protocols are independent of the physical interface they run on. Furthermore, the switch includes a generic forwarding interface software for hiding the details of transmitting and receiving packets over different interface types.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MULTI-SERVICE NETWORK SWITCH

FIELD OF THE INVENTION

The present invention relates generally to network switches, and more particularly, to a multi-service network switch for providing multiple network services from a single platform.

BACKGROUND OF THE INVENTION

Today's network service providers face extraordinary challenges. Traffic levels are rapidly increasing. Both consumers and corporations are demanding higher access rates and staying on the Internet longer while looking for predictable performance and stringent service-level guarantees. This puts direct demands on Internet Service Providers (ISPs) to provide larger capacity and higher speed at their point of presence (POP) locations, preferably without compromising performance.

Just to maintain acceptable performance, service providers are adding support for more users, more traffic, and more transactions, preferably without introducing bottlenecks or compromising network availability. Many network-based businesses transactions are time-critical and typically cannot tolerate undue delay or disruption.

In an effort to meet some of the challenges, some ISPs turn to access concentrators and high-end routers to handle the high density traffic. However, the problem with traditional access concentrators and high-end routers is that they are designed with a central CPU for centralized processing. All data is passed through a centralized route forwarder/processor which increases processing overhead, causes bottlenecks, inhibits scalability, and provides a single point of failure. Essentially, the central processor cannot effectively process the increased amount of data traffic when new modules are added. As more modules are added system performance hits a wall.

In addition to the challenge of growing traffic levels is the challenge of growing diversity of network technology. Users may access the public infrastructure, for example, over dial-up connections, ISDN links, leased lines, frame relays, ATM virtual circuits. They may use voice-grade modems, cable modems, a variety of xDSL modems, or other modems. Within the infrastructure, a service provider's POP may attach to the core network and to other devices in the POP using, for example, ATM, frame relay, or Ethernet.

Supporting each type of network technology in a traditional manner means that the ISPs typically add separate access servers, access routers, and/or stand alone LAN switches, generally resulting in an increase in cost and management complexities for the ISP.

Accordingly, there is a need for network switch capable of providing fault-tolerant and efficient services that will accommodate the increase in the number and the variety of network traffic. Such a switch should preferably allow ISPs to provide value added-services, allowing

1 them to differentiate themselves from the competition, taking them into new markets, and
boosting revenue from existing customers.

SUMMARY OF THE INVENTION

5 The present invention is directed to a multi-service network switch capable of providing
multiple services including modem and ISDN services, frame relay support, LAN interfaces, and
layer-2 and layer-3 switching, from a single platform. According to one embodiment of the
invention, the switch incorporates a distributed packet forwarding architecture where the various
system interface modules (cards) have on-board intelligence, route forwarding, and route
10 processing information. Each module is therefore able to independently make forwarding
decisions, allowing the packets to be forwarded in parallel. According to one aspect of the
invention, distributed packet forwarding is accomplished by a hierarchical routing scheme
including a routing table, a forwarding table, and an IP cache. Each interface module preferably
includes the IP cache and forwarding table of known destination addresses. If a destination
15 address is not found in either the IP cache or the forwarding table, a lookup is done in the routing
table and routing information is obtained for forwarding a packet.

In alternative embodiments, the switch includes one or more of the following features:

The switch allows for dynamic resource management for dynamically assigning resources
to an incoming call. In this way, resources are not tied to specific ports, but may be shared
20 among various interface modules. If a resource is available anywhere on the system, any card
may preferably use it. Furthermore, if one of the resources fails, it is marked unavailable, and
calls are preferably directed automatically to other resources. With a fully distributed
architecture, this reduces reliance on a single processing unit for transmitting or responding to
a resource request.

25 The switch may also include fault management features to guard against single points of
failure within the switch. A fault tolerant application manager (FTAM) monitors system
modules, and if one module goes down, the FTAM software in the remaining modules preferably
recovers from the failure, re-routing connections to different resources or output ports.
Preferably, the FTAM invokes automatic protection switching (APS) hardware and software for
30 automatic recovery from both equipment faults and external link failures.

The switch may further facilitate dial network wholesaling where dial ports are resold to
other ISPs, by partitioning the switch into multiple virtual routers. Each virtual router should
preferably have its own set of resources (e.g. ISDN or modem resources) and a routing table
proprietary to the virtual router. Each virtual router therefore preferably functions as a separate
35 router in an independent and self-contained manner. According to one specific aspect of the
invention, each virtual router is further partitioned into virtual private networks for further
controlling access to the network. A virtual private network is created via filters where each filter

1 is associated with a filtering criteria and an action to be taken upon a match of the filtering criteria by a block of data directed to the virtual router.

Dial network wholesaling is also supported by the switch's policy-based routing. The switch allows the selection of a routing path for a particular connection based on call policies associated with the call. Thus, a connection may be established to a particular wholeselling ISP's router based on factors such as the type of inlink of the connection, a domain name, a telephone number, and the like.

5 The switch also provides tiered access of the Internet by defining quality of access (QoA) levels to each incoming connection request. The QoA levels allow the switch to prioritize the incoming connection requests when there is competition for resources. Preferably, a connection request with a higher QoA level is given a higher priority than a connection request with a lower QoA level.

10 The switch may further support an IP routing protocol and architecture in which the layer two protocols are independent of the physical interface they run on. A port interface (PIF) module enables dynamic bonding of layer two protocols to physical interfaces. When a connection is made on the physical port, the switch creates a PIF object for the port. The PIF object preferably determines the layer two protocol to be utilized for the session based on the type of connection, and dynamically bonds a layer two interface to the layer one interface of the media port. In this way, layer two protocols need not be made dependent on the physical media ports on which they run, but may be determined dynamically at runtime. When a packet is to be forwarded to a physical port, for example, the PIF receives the packet, adds the required layer two encapsulation headers, and forwards the packet to the appropriate physical interface.

20 The switch may further include generic forwarding interface (GFI) software for application transparency. The GFI software preferably provides a uniform interface to the forwarding functions to mask the details of transmitting and receiving packets over different interface types. It also preferably defines an interface for the drivers to deliver received packets and transmit packets from the system.

BRIEF DESCRIPTION OF THE DRAWINGS

30 These and other features, aspects and advantages of the present invention will be more fully understood when considered with respect to the following detailed description, appended claims and accompanying drawings wherein:

FIG. 1 is a schematic block diagram of a multi-service network switch according to one embodiment of the invention;

35 FIG. 2 is a more detailed schematic block diagram of a forwarding module of FIG. 1;

FIG. 3 is an exemplary flow diagram for processing a call coming into the switch of FIG.

1;

FIG. 4 is a more detailed functional block diagram of an IP forwarder module of FIG. 2;

- 1 FIG. 5 is a schematic layout diagram of a routing table;
FIG. 6 is a schematic layout diagram of a forwarding table;
FIG. 7 is a schematic layout diagram of an IP cache;
FIG. 8 is a schematic layout diagram of an ARP table;
- 5 FIG. 9 is a flow diagram of a packet forwarding process engaged by the IP forwarder module of FIG. 4;
- FIG. 10 is a schematic layout diagram of a domain database;
FIG. 11 is a schematic layout diagram of a call policy record;
FIG. 12 is a process flow diagram for policy based routing;
- 10 FIG. 13 is a schematic layout diagram of a quality of access table;
FIG. 14 is an illustration of a path that a connection might take if switch resources are being shared;
- FIG. 15 is a schematic layout diagram of a modem resource table;
FIG. 16 is a flow diagram of a resource allocation process;
- 15 FIG. 17 is a schematic block diagram of the switch of FIG. 1 maintaining a routing table for each virtual router;
- FIG. 18 is a schematic layout diagram of a sessions table including various virtual private network sessions;
- FIG. 19 is a schematic layout diagram of a rules table including various virtual private network rules;
- 20 FIG. 20 is a schematic layout diagram of a filter table including various virtual private network filters;
- FIG. 21 is a flow diagram of a packet filtering process engaged by a filtering module;
- FIG. 22 is a schematic block diagram of a switch incorporating an APS mechanism for
- 25 external link failures;
- FIG. 23 is a schematic block diagram of a switch incorporating a backup port that is physically connected to another port on a separate card;
- FIG. 24 is a schematic block diagram of a switch incorporating a 1:2 protection switching;
- FIG. 25 is a schematic block diagram of a switch incorporating a 1:2 protection switching
- 30 according to an alternative embodiment of the invention;
- FIG. 26 is a schematic block diagram of a switch incorporating a 1:1 protection switching;
- FIG. 27 is a schematic block diagram of an IP forwarding layer, layer two protocols, and layer one physical interfaces;
- FIG. 28 is a schematic block diagram showing layer one, two, and three interfaces with
- 35 multiple port interfaces;
- FIG. 29 is a schematic block diagram of a generic forwarding interface dividing the switch of FIG. 1 into drivers and applications;

1 FIG. 30 is a schematic block diagram of a generic packet format;

 FIG. 31 is a schematic layout diagram of a forwarding port address;

5 FIG. 32 is a schematic layout diagram of a physical port address;

 FIG. 33 is a schematic layout diagram of an input port information;

10 FIG. 34 is a schematic layout diagram of an output port information;

 FIG. 35 is a schematic layout diagram of virtual address port assignments; and

15 FIG. 36 is a schematic layout diagram of a generic forwarding interface supporting receiving queues and forwarding queues.

DETAILED DESCRIPTION OF THE INVENTION

I. MULTI-SERVICE NETWORK SWITCH SYSTEM ARCHITECTURE

20 FIG. 1 is a schematic block diagram of a multi-service network switch (also referred to as the "chassis" or "system") according to one embodiment of the invention. Each slot on the switch preferably accommodates a single interface module (a card), referred to as a forwarding module (FM) 10. Each FM 10 preferably includes the on-board intelligence, route forwarding, and route processing information for distributed packet forwarding, as is described in further detail below.

25 One type of FM, referred to as a system control module (SCM) 14, hosts a route server and acts as the control point for network management. The SCM 14 also performs all the typical functions of an FM 10.

30 The switch includes at least two SCMs for fault tolerance, a primary SCM and a secondary SCM. The primary SCM is chosen at system startup, and announced to all the other FMs 10. The primary SCM preferably selects the secondary SCM as backup. If the primary SCM fails, the secondary SCM automatically takes over as primary, preferably with no loss of information and no interruption of service.

35 Each FM 10 may have associated application-specific daughter cards, referred to as personality modules (PMs) 12, for additional physical line interfaces or support hardware. In the preferred embodiment, there are one or two PMs associated with each FM. Exemplary PMs 12 include Ethernet switch PMs 12a, primary rate interface PMs 12b, digital modem server PMs 12c, and serial data interface PMs 12d. Together, the FMs 10 and PMs 12 allow an ISP to

1 provide a wide range of services and support a wide range of applications, all within a single platform.

5 The Ethernet switch PM 12a enables a LAN connection to a public network, such as the Internet. This module is typically used to connect server farms, intranets, and Web servers to the Internet. According to one embodiment of the invention, the Ethernet switch PM 12a provides twelve 10 Mb Ethernet ports and two 10/100 Mb auto-sensing Ethernet/fast Ethernet ports.

10 The primary rate interface (PRI) PM 12b provides dial-up connections to the Internet. This module may be provided in software for either T1/E1 links or PRI ISDN links. The PRI PM 12b provides redundant connections for automatic protection switching on every port. Port "A" 13 is assigned as the active primary port and Port "B" 15 is assigned as the live backup port.

15 The digital modem server PM 12c provides dial-up access for modem calls. According to one embodiment of the invention, each digital modem server PM 12c provides a modem pool of 32 modems. The digital modem server PM 12c preferably has no physical connectors. Thus, incoming calls are routed via the backplane to the FM 10 on which the digital modem server PM 12c is connected. The available modems are allocated to the incoming calls based on resource availability criteria such as quality of access and virtual router ID. If a call is capable of being served, the call is assigned randomly to one of the available modems in the modem pool regardless of the FM 10 in which the call came in.

20 The serial data interface PM 12d enables serial synchronous communication. The serial data interface PM 12d supports a total of four links, for example, three frame relay and one Ethernet link, or four frame relay links and no Ethernet links. The link layer on the serial data interface PM 12d is preferably frame relay, and it typically connects to local routers or external equipment for connections to ISPs or service providers.

25 In addition to the application specific PMs 12d, dedicated FMs 10 may also enable the ISPs to provide a wide range of services. Dedicated FMs are preferably fixed configuration modules with processing power and functions hardwired onto the module. Exemplary dedicated FMs include digital modem server FMs and WAN line interface FMs. A WAN line interface FM provides channelized T1 or primary rate ISDN access to the switch. A digital modem server FM provides dial-up access for modem calls. A digital modem server FM typically provides 32 modems, but with the addition of a digital modem server PM 12c, it may provide up to 64 modems.

30 The switch preferably includes a redundant bus architecture for interconnecting the FMs 10 and the SCMs 14. This bus architecture preferably provides two (right and left) management busses 16, two (right and left) time-division multiplexed (TDM) busses 18, and two (right and left) cell/ATM busses 20, on the switch's backplane. In one embodiment of the invention, all cards use the right management and TDM busses by default. All cards in even slots use the left cell bus by default, and all cards in odd slots use the right cell bus by default. The redundant bus architecture enables traffic to be automatically switched to the remaining bus to ensure continued

1 service. When operation of the failed bus is restored, the traffic is preferably automatically switched back to the newly restored bus.

5 The management busses 16 provide internal system communication for monitoring various system components. For instance, the management busses carry messages for power-up sequencing, module status, and other hardware management functions.

The TDM busses 18 provide communication for the digital modem server PMs 12c. According to one embodiment of the invention, the TDM busses 16c support over 2,000 DS0 connections and share the traffic load communicated on them.

10 The cell busses 20 move user traffic between the FMs 10, and carry internal protocol and control messages using multicast circuitry.

In addition to the above, the switch also includes two clock cards, a right or first clock card 18a, and a left or second clock card 18b, either of which may be designated as an active primary clock card or a redundant backup clock card. The right clock card 18a monitors the right TDM and cell busses, and the left clock card 18b monitors the left TDM and cell busses.

15 Both clock cards periodically check their respective TDM and cell busses, as well as the status of system fan trays, system fans, and presence and type of power supplies. The clock cards then periodically broadcast to all the FMs 10 a chassis status message via its management bus 16.

20 The clock cards are preferably provisioned with at least one clock source in order for the switch to receive dial-up calls. The clock preferably forces the transmitted and received bits to remain synchronized. According to one embodiment of the invention, the switch supports up to five reference clocks, one live primary, one secondary for redundancy, and up to three alternatives. The switch may derive the reference clock from either an external source or an internal system clock. If the input from one source becomes unacceptable, the clock card
25 automatically switches to a backup clock source. Similarly, if a clock card or TDM bus fails, the other card or bus takes over.

FIG. 2 is a more detailed schematic block diagram of the FM 10 of FIG. 1. Although FIG. 2 is described in terms of the FM 10, the same block diagram may also apply to the SCM 14 since the SCM 14 is a specific type of FM 10. The SCM 14, however, may include additional
30 memory, flash PROMs, and boot PROMs. According to one embodiment of the invention, the FM 10 includes at least one, but generally two, RISC processors: a right or first processor (RCPU) 22a (also referred to as the application CPU), and a left or second processor (LCPU) 22b (also referred to as the driver CPU). In a preferred embodiment having two CPUs, the LCPU 22b is mainly responsible for receiving and transmitting packets, and the RCP
35 CPU 22a is mainly responsible for fault management, protocol encapsulation/decapsulation, and the like. Both the RCP 22a and LCPU 22b have access to a shared memory 24 through Peripheral Component Interconnect (PCI) busses 28a, 28b.

1 A PCI bridge 30 connects the right PCI (RPCI) bus 28a to the left PCI (LPCI) bus 28b. The RPCI bus 28a is preferably the primary PCI bus with respect to the bridge 30, and the LPCI bus 28b is the secondary PCI bus.

5 Each FM 10 preferably also includes a generic module management (GMM) 26 block for exchanging messages with the RCP 22a across the management bus 16. According to one embodiment of the invention, the GMM 26 is implemented as an intelligent microprocessor. Communication between the GMM 26 and the RCP 22a is effectuated through a set of registers. The registers are implemented in a programmable logic device and accessed by the RCP 22a through a PCI input/output 40 block. According to one embodiment of the invention,
10 the GMM 26 provides two status registers, GST0 and GST1, by which the RCP 22a polls and obtains information regarding the chassis status, status of last command issued, status of previous and current messages in the message queues, and the like.

 The GMM 26 receives broadcast messages from other GMMs as well as messages addressed to its FM 10 via the management bus 16. According to one embodiment of the
15 invention, only the GMM 26 on a card that is designated as a chassis manager receives broadcast messages. All other GMMs preferably ignore the broadcast messages and receive only those messages addressed to the card. Special processing is done by the GMM 26 resident on the chassis manager for chassis status messages periodically broadcast by the clock cards 18a, 18b, as is described in further detail below.

20 Any card, be it an FM 10 or SCM 14, may be designated as the chassis manager. However, there is only one active chassis manager, a primary chassis manager, for the entire system. If the primary chassis manager goes down, a backup secondary chassis manager takes over as the active chassis manager.

 Selection of the primary chassis manager and the secondary chassis manager preferably
25 occurs during power-up of the system. Each card includes a chassis management switch, and all cards with the chassis management switch turned on are chassis manager candidates. These candidates power-up without any need of sending activation requests. According to one embodiment of the invention, the card in the lowest slot of the chassis with the chassis management switch turned on is selected as the primary chassis manager, and the card in the
30 second lowest slot of the chassis with the chassis management switch turned on is selected as the secondary chassis manager. If only one card exists in the system, it becomes both the primary chassis manager and the secondary chassis manager. Once the primary and secondary chassis managers are elected, these cards begin responding to activation requests received from the other cards.

35 The primary and secondary chassis managers communicate via hello messages over the cell bus 20. The primary chassis manager controls the right active management and cell busses 16a, 20a. The secondary chassis manager controls the left standby management and cell busses 16b, 20b. If the secondary chassis manager detects a failure of the primary chassis manager (due

1 to timeout of the hello messages), the secondary preferably switches over to the right
management bus 16a, resets the primary chassis manager, and becomes the new primary chassis
manager. The new primary chassis manager selects a new secondary chassis manager based upon
5 chassis manager, the primary chassis manager resets the secondary chassis manager and selects
a new FM 10 to act as the secondary chassis manager.

The chassis manager includes a chassis management module (CMM) 34. The CMM 34
receives and transmits chassis status messages via the GMM 26, and is responsible for
monitoring and managing the system. Among other things, the CMM 34 is responsible for
10 chassis power management. Thus, when a new FM 10 is inserted into the system, the GMM 26
of the newly inserted card reads a serial EEPROM in the FM 10 and PMs 12 for determining
their power requirements. The EEPROM stores information about the model, revision, serial
number, and power requirements of the card. The new card's GMM 26 then broadcasts the
power requirement in an activation request message on the management bus 16 to the chassis
15 manager. The GMM 26 in the chassis manager receives the request and passes it on to the CMM
34 for determining if there is sufficient power in the system to bring up the card. If there is, the
GMM 26 in the chassis manager answers with an activate module message.

The CMM 34 in the chassis manager is preferably also responsible for clock card
monitoring. The CMM 34 in the primary chassis manager listens for the chassis status messages
20 periodically sent by the right clock card via the right management bus 16a, and the CMM 34 in
the secondary chassis manager listens for the chassis status messages periodically sent by the left
clock card via the left management bus 16b. The chassis status messages include the status of
chassis power supplies, fans, and temperature. The GMM 26 in each chassis manager monitors
its respective management bus for the chassis status messages. The GMM 26 then notifies the
25 CMM 34 of any change in the chassis status message. If power is a limiting resource, the CMM
34 powers down cards starting from the highest numbered slots until power consumption
requirements can be met by the power supplies still operational in the system.

If the GMM 26 does not receive two successive chassis status messages on a particular
management bus, the GMM informs its CMM 34. The CMM 34 then invokes the FTAM 36 to
30 broadcast out a test message on its management bus. If the transmission succeeds, or if the
transmission fails due to unavailability of the destination, its clock card (e.g. the right clock card
18a) is assumed to have incurred a fault and the FTAM 36 generates a fault notification. All
cards are then moved to the standby management bus (e.g. the left management bus 16b). When
the faulty clock card is back in service, all cards are preferably moved back to original
35 management bus (e.g. the right management bus 16a).

If the transmission fails due to bus unavailability, then the management bus being
monitored (e.g. the right management bus 16a) is deemed to have incurred a fault, and the FTAM
36 generates a fault notification. The corresponding chassis manager moves all cards to the

1 standby management bus (e.g. the left management bus 16b). The faulty management bus is monitored, and when back in service, all cards are, preferably moved back to this bus.

Management and monitoring of the chassis by the CMM 34 is done in conjunction with the FTAM 36 running in the chassis manager. An instance of the FTAM 36 also runs in each of
5 the other cards in the chassis. Whereas the CMM 34 is responsible for the entire chassis, the FTAM 36 is preferably responsible for recognizing faults and acting on some of the faults that are local to the card. Among other things, FTAMs 36 provide local monitoring, fault detection, fault notification, fault isolation, and service restoration (wherever possible) for card failures and link/port failures.

10 Application software components register with the FTAM 36 identifying events to be monitored. When a fault is detected, the FTAM 36 notifies all applications that have registered for that type of event. The FTAM 36 and the applications then take corrective action. For instance, a clock manager application may register with the FTAM 36 for selection of external clock sources on active links. A redundant port list application may register with the FTAM 36
15 for determining faulty links and switching over to active backup ports. IP applications may register with the FTAM 36 for updating forwarding tables with failed link/port entries.

Each FTAM 36 detects a card failure via hello messages. Each FM 20 sends out a hello message at fixed time intervals over the cell bus 20. If a card does not send hello messages, the other cards in the system mark this card as being down. The FTAM 36 in each card then updates
20 all tables impacted by the failure event. The primary SCM 14, upon detecting the card failure, issues a reset request over the management bus to the primary chassis to restart the defective card.

Each FTAM 36 also preferably detects link/port failures. Link and port drivers constantly monitor the state of each link and port. If a change in state is detected, a link failure broadcast
25 message is sent to the FTAM 36. The system's automatic protection switching (APS) hardware and software mechanisms allow automatic recovery from both equipment faults and external link failures. For example, each port on the primary rate interface (PRI) PM 12b (FIG. 1) has two connectors, a Port "A" 13 connector and a Port "B" 15 connector. If an internal fault is detected on Port "A" 13, the system's APS mechanism automatically redirects WAN traffic through the
30 Port "B" 15 connector.

Referring again to FIG. 2, each FM 10 further includes a connection manager 46 and a resource manager 38. The connection manager 46 detects incoming calls to the FM 10 and the resource manager 38 manages and allocates local resources including digital modem and ISDN
switched resources. Each connection to the switch needs a specific set of hardware and software
35 resources. A frame relay call, for example, needs a line interface, an HDLC controller, a frame relay protocol stack, and frame forwarding software. Generally, all the resources required for a connection are found on the input FM 10 and its associated PMs 12. Sometimes, however, traffic entering the system on one card requires resources on another. Thus, when the connection

1 manager 46 detects an incoming call, a resource request is broadcast over the cell bus 20. The resource manager 38 in each card receives the request and determines what resources are needed. If the card has the requested resource, it is allocated to the incoming call.

5 Each FM 10 also includes an IP forwarder 44 for forwarding packets based on layer three addresses. The IP forwarder module preferably contains local routing information for forwarding a packet via a right, or first, IP forwarding engine 42a and a left, or second, IP forwarding engine 42b. When a packet is received by the FM 10, the IP forwarder 44 proceeds to forward the packet if it has learned the destination address. Otherwise, the IP forwarder 44 performs a lookup of a central routing table and obtains the necessary routing information.

10 FIG. 3 is an exemplary flow diagram for processing a connection request coming into the switch of FIG. 1. The program starts, and in step 50, the connection manager 46 detects an incoming call in one of the physical ports of the FM 10 (the receiving FM). In step 52, the connection manager 46 notifies the resource manager 38 in the receiving FM 10 of the incoming call. The resource manager 38, in step 54, searches a call policy database for a call policy record
15 corresponding to the incoming call. The call policy record includes various parameters which dictate how the call is to be routed. Different policies may be applied based on the inlink of the call, a telephone number, a domain name, a source address, a destination address, and the like.

Included in the call policy parameters are a quality of access (QoA) level, quality of service (QoS) level, virtual router ID, and virtual private network ID associated with the call.
20 QoA is a method of classifying users and granting access to the switch based on a comparison of their QoA level to the current resource utilization. This allows for tiered access to the Internet when there is a competition for resources. Each QoA level is preferably assigned a percentage of threshold resource usage. If resource utilization is below the percentage of threshold resource usage assigned to the incoming call's QoA level, the call is accepted. Otherwise, the call is
25 rejected.

QoS is a method of classifying users to determine the priority with which packets are conveyed once a call has been accepted. QoS offers preferential treatment by processing connections based on their QoS levels. The higher the QoS level attached to the call, the higher the processing priority given to the packets associated with the call.

30 The incoming call's virtual router ID and virtual private network ID allow the switch to provide access to resources that the user authorized for. According to one embodiment of the invention, the switch may be partitioned into multiple virtual routers where each virtual router has its own set of resources (e.g. ISDN or modem resources) and routing tables. Thus, each virtual router preferably functions as a separate router in an independent and self-contained
35 manner. Each virtual router may further be partitioned into multiple virtual private networks (VPNs) for further controlling access to the switch. VPNs are created with filtering software that filters traffic directed to the virtual router based on criteria such as, for example, source address and/or destination address.

1 Once a call's QoA level, QoS level, virtual router ID, and VPN ID have been identified
from the call policy record, the resource manager 38, in step 58, broadcasts a resource request
message to the other FMs 10. If any of the FMs 10 have an available resource that matches the
call's QoA level and virtual router ID, the FM 10 with the available resource transmits a response
5 to the receiving FM 10 for connecting the call to the available resource.

 If the incoming call is accepted, the program, in step 59, creates a port interface (PIF)
object that determines the layer two protocol to be utilized for the session. A generic forwarding
interface provided by the switch then dynamically bonds the layer two interface to the layer one
interface of the physical port. In this way, layer two protocols need not be made dependent on
10 the physical media ports in which they run on, but may be determined dynamically at runtime.

 In step 60, the program invokes the ISP's authentication server for authenticating the user.
A typical authentication server is a RADIUS server. The authentication server preferably
includes a database of users and user configuration information detailing the type of service to
15 deliver to each user. Service configuration information may include the type of compression,
QoA level, QoS level, and/or a VPN ID assigned to the user, as is described in further detail
below. According to one embodiment of the invention, the configuration information in the
authentication server may override default configuration information provided through the call
policy database.

20 After the user has been authenticated, data packets may be forwarded to their destination
addresses as indicated by step 62. In this regard, the switch provides for a uniform interface,
called a generic forwarding interface (GFI), responsible for all internal packet forwarding, either
between ports on the same FM 10 or across the bus to another FM 10 in the switch. Specifically,
the GFI software provides for transparency between applications and link protocol, and the
25 physical link driver, so that any physical interface may be associated with any protocol or
application. Thus, all GFI forwarding functions are preferably protocol transparent.

 When a packet arrives into the system, the GFI software translates the packet into a
generic format using GFI utilities. When the packet is to be transmitted to a physical port, the
GFI software invokes the appropriate driver's forwarding function to transmit the packet. The
30 driver's forwarding function is then responsible for identifying the physical port and passing the
packet to the PIF module for translating the generic packet into the driver's specific format and
transmitting it out the required port.

 Before forwarding the data packet, however, a check is preferably done to determine
whether there are filters to be applied to the data packet. The filters determine whether the packet
35 is to be forwarded or dropped. The filters applicable to the data packet are located based on the
packet's VPN ID.

II. DISTRIBUTED PROCESSING AND PACKET FORWARDING

1 One of the features of the multi-service network switch of FIG. 1 is IP (layer three) routing using a distributed processing and packet forwarding architecture. The IP forwarder module 44 in each FM 10 provides the necessary packet forwarding and route processing intelligence. Unlike a traditional access server where a centralized processor creates a bottleneck, a distributed forwarding architecture helps to reduce or eliminate the single point of congestion and allows the products to scale for both the number of connected interfaces and for packet forwarding performance.

FIG. 4 is a more detailed functional block diagram of the IP forwarder module 44 of FIG. 2. An IP data packet arrives at a media port of a PM 12 and is processed by its media port driver 118. The IP data packet may also be received by a backplane driver 120 if, for example, the packet has been forwarded by another FM 10 via the cell bus 20.

When a connection is made on the media port, the switch creates a port interface (PIF) 122 object for the port. The PIF 122 object determines the layer two protocol to be utilized for the current session based on the type of connection, and the GFI software 124 dynamically bonds the layer two interface to the layer one interface of the media port. In this way, layer two protocols need not be made dependent on the physical media ports in which they run on, but may be determined dynamically at runtime.

The PIF 122 also includes PIF structures for storing specific media and packet format information for each port. PIF structures are maintained as two dimensional arrays using a controller number and a port number as the index.

A logical port identifier (LPI) 128 communicates with the PIF 122 and includes the IP parameters related to each physical port. The IP layer calls an LPI transmit function whenever it wants to transmit a packet. The LPI transmit function identifies the appropriate physical port and passes the packet to the PIF 122 for adding the media specific layer two encapsulation headers and transmitting it out from the appropriate port.

When a packet is received by the media port driver 120, the packet is preferably translated by the driver to a generic format and transmitted to the GFI 124 software. GFI 124 preferably handles all internal packet forwarding in a protocol transparent layer, hiding the details of transmitting and receiving packets over different interface types. GFI 124 further queues the packet in one of four GFI buffers resident in the system shared memory 24 (FIG. 2) based on the packet's QoS.

A packet processing module 126 polls the GF2 buffers for the packet, and parses the packet for locating the packet's PIF structure. Once located, the packet processing module 126 preferably checks that the packet is a data packet, checks that a session is established, and hands the packet over to the IP forwarder 44. If the packet needs to be routed, the IP forwarder tries to obtain the destination information from its IP cache 102 or forwarding table 90. If unsuccessful, the IP forwarder 44 attempts to obtain the information from a routing table 70 stored in the SCM 14. In addition, the IP forwarder 44 might obtain additional parameters for the destination

1 address from an address resolution protocol (ARP) table 112 through an ARP function block 114; or through a management ARP (MARP) request via a MARP function block 116.

FIG. 5 is a schematic layout diagram of a routing table 70 according to one embodiment of the invention. The routing table 70 includes a list of all of the IP destination addresses reachable from the FMs 10, and all known routes to each destination address. The routing table
5 may be created based on standard routing protocols including RIP, OSPF, BGP4, and the like.

According to one embodiment of the invention, the routing table 70 includes a destination field 72 identifying a configured destination IP address to where a packet might be forwarded. The routing table also includes a subnet field 74 indicating the significant bits of the destination
10 IP address by either hiding or showing part of the address. The number "0" allows the corresponding bits of the IP address to be shown when the number "255" hides the corresponding bits of the IP address. In this way, a range of addresses in the subnet may be specified.

The routing table 70 further includes a next hop router field 76 indicating an IP address to a next hop router. An owner field 78 indicates how the route was learned. Specifically,
15 "OSPFE" indicates that the route is an external route learned from a different routing domain (e.g. RIP). "OSPF1" indicates that the route is an intra-area route. "OSPF2" indicates that the route is an inter-area route. "LOCAL" indicates that the route is directly-connected. "STATIC" indicates that the route is a manually-configured route. "DIAL-POOL" indicates that the route is assigned out of a dial-up pool.

20 A cost field 80 indicates a cost associated with each route. The cost is based on a distance metric to the destination IP address using the indicated route. Generally, the cost is calculated using any suitable or conventional distance vector algorithm.

FIG. 6 is a schematic layout diagram of a forwarding table 90 according to one embodiment of the invention. The forwarding table 90 is a subset of the routing table 70. Unlike
25 the routing table 70, however, the forwarding table 90 preferably includes a list of IP destination addresses and the best known route to each of these destination addresses.

As with the routing table 70, the forwarding table 90 includes a destination field 92 and a subnet field 94 respectively indicating IP destination addresses and subnet masks. A next hop router field 96 indicates an IP address to the next hop router if the route is a remote route.

30 A type field 98 indicates a type of port connection. For instance, if the type of connection is indicated as "SPORT," the destination IP address is on a single port. If the type of connection is indicated as "VLAN," the destination is part of a virtual LAN. If the type is indicated as "DIAL," the destination port exists in the dial-up IP address pool.

The forwarding table also includes a flag field 100 for describing the types of route. Valid
35 values for this field are "S" indicating a system interface where the destination exists on the far side of a switch interface; "D" indicating a direct interface where the destination is connected to the switch (either on the same card or on a different card); "R" indicating that the destination is remote on another device of the network; "P" indicating that the destination is a supernet; "F"

1 indicating that the destination is a default route; and "M" indicating that the destination is a management interface.

FIG. 7 is a schematic layout diagram of an IP cache 102 according to one embodiment of the invention. The IP cache 102 also resides in each of the FMs 10 and includes a list of the most recently used IP source/destination address pairs, along with the physical port address and header information. Thus, if a destination address exists in the IP cache, packets may be forwarded without lookup of any routing or forwarding table, allowing increased forwarding performance.

According to one embodiment of the invention, the IP cache 102 includes a destination field 104 and a source field 106 indicating recent IP destination and source addresses. An out port field 108 indicates a physical port on which data is transmitted to the destination address. A header field 110 indicates 16-bits of MAC header information for forwarding the packet to the destination address.

FIG. 8 is a schematic layout diagram of an ARP table 112 according to one embodiment of the invention. The ARP table allows the resolution of IP addresses to MAC addresses and physical port addresses for local destinations. When a device is connected to the FM 10, the IP software dynamically resolves the MAC-to-IP address translation and stores this information in the FM's 10 ARP table 112.

The ARP table 112 includes an IP address field 200 indicating an IP address to be translated to a MAC address and to a physical port address. A MAC address field 202 indicates the MAC address corresponding to the IP address. A physical port field 204 indicates the physical port address corresponding to the IP and MAC addresses. According to one embodiment of the invention, the port address convention is as follows:

device type.chassis.slot.PersonalityModuleLocation.link.port

The device type is a two-character description of the type of PM 12 providing the connection. The switch preferably supports at least the following PMs: primary rate interface PMs 12b for ISDN (is); primary rate interface PMs 12b for T1 (t1); digital modem server PMs 12c (mo); Ethernet switch PMs 12a (en); and serial data interface PMs 12d for frame relay (fr).

The chassis number is a number assigned to the switch. The slot number is where the FM is inserted. Slots are numbered sequentially from bottom to top starting from slot number one. The personality module location indicates either a right PM (number 1) or a left PM (number 2). The link specifies the number of logical links configured on the module. The port number indicates a port on the PM. Thus, according to this connection, physical port address En 1.3.1.1.1 indicates a connection to an Ethernet module, in chassis 1, on slot 3, on the right PM, on link 1, and physical port 1.

1 The ARP table 112 also includes a type field 206 indicating that the address is static ("S") if the address was statistically configured in a network, local ("L") if the address is on a directly-connected network, dynamic ("D") if the address was learned, remote ("R") if the address was on a remote network, point-to-point ("P") if the address was learned on a point-to-point link, a
5 router ("T") if the address belongs to a router, or broadcast ("B") if the address was learned through a broadcast packet.

 FIG. 9 is a flow diagram of a packet forwarding process engaged by the IP forwarder 44. When an IP packet that needs to be routed is handed to the IP forwarder 44, the program inquires in step 210 whether the IP cache 102 includes the destination address. If an entry for the
10 destination address exists in the IP cache 102, the MAC header is copied from the header field 110 onto the packet, and the packet is forwarded, in step 212, to the physical port indicated by the out port field 108. The backplane driver 120 is utilized to forward the packet if the physical port resides on a different card.

 If there is no entry for the destination address in the IP cache 102, the program inquires
15 in step 214 whether the destination address is in the IP forwarding table 90. If the answer is YES, the program retrieves the route to the destination and determines whether the route is via one of the ports on the same card or through another card. If the route is via one of the ports on the same card, it may be handled locally. Accordingly, the program, in step 216, searches the ARP table 112 for the destination address if it is directly attached, or for the next hop router obtained
20 from the next hop router field 96 of the forwarding table 90 if it is a remote route. If either the destination address or the next hop router is found in the ARP table 112, as inquired in step 218, the packet is sent to the indicated physical port address, and the entry is added to the IP cache 102.

 If there is no entry in the ARP table for the destination address or the next hop router, then
25 the destination is not via one of the ports on the same card. Thus, the program, in step 220, invokes a management ARP (MARP) protocol to discover whether the destination is through a port on a different card. The program thus places a MARP request packet in front of the IP packet and broadcasts it out on the management bus 16 to find if another FM 10 has the path to the destination. The FM 10 with the destination IP route strips off the MARP packet and
30 forwards the IP packet out the appropriate interface. A MARP response packet is then sent back to the originating FM 10 so that its ARP table 112 may be updated with the port information as is indicated in step 222. All subsequent packets may now be forwarded directly to the port and not broadcast onto the bus.

 Referring back to step 214, if the destination address is not in the forwarding table 90, a
35 request for the route is sent to the SCM 14. In step 224, the program inquires whether the destination address exists in the routing table 70. If the answer is YES, the route to the destination address is retrieved and stored in the forwarding table in step 226. If multiple routes exist to the same destination, the SCM 14 preferably returns the route with the lowest cost. If

1 multiple routes exist to the same destination and both routes have the same cost, the SCM 14 returns whichever route appears first in the routing table 70. The program then performs either an ARP table lookup or invokes the MARP request to forward the packet to the destination address.

5 If the destination address is not in the routing table, the SCM 14, in step 228, returns a message indicating that the destination was unreachable, and the packet is dropped in step 230.

III. POLICY BASED ROUTING

Another feature of the multi-service network switch of FIG. 1 is the ability to select
10 a router based on certain characteristics of a connection request. Such characteristics include, but are not limited to, an inbound access channel or link, a calling or called telephone number, a domain name, a source address, a destination address, and the like. Among other things, this feature facilitates the wholesaling of dial-up connections to other ISPs. For example, all user traffic received by a particular type of inlink (e.g. an ISDN line) may be directed to the router
15 operated by a wholesaling ISP designated to the inlink. Thus, policy based routing allows a routing path to be selected within the switch without having to refer to a separate routing table.

For domain-based routing, a user's login information (e.g. "user@isp1.com") may be used to select an ISP and authenticate the user with the ISP's authentication server. Once authenticated, all packets originated by the user are forwarded to the router designated for the
20 domain operated by the ISP.

According to one embodiment of the invention, the switch maintains a domain database including parameters that determine the domain to which the user is to be connected. FIG 10 is a schematic layout diagram of a domain database 380 according to one embodiment of the invention. Each domain database 380 is headed and identified by a domain name 382 that a user
25 may specify to be connected. The domain database 380 also includes a next hop router's address 384 identifying a router designated for the domain. Packets originated by the user connected to the domain are then forwarded to the specified router.

For source-based routing, packets are forwarded to a specific router based on the source address of the packet. Thus, the user with a specified source address preferably only accesses the
30 domain which is behind the designated router. According to one embodiment of the invention, router information for source-based routing is set-up for each user in the ISP's authentication server.

For call-policy-based routing, packets are forwarded to a specific router based on a telephone number, link, or channel of a dial-up connection. According to one embodiment of
35 the invention, the switch maintains a call policy database including call profile information, referred to as call policy parameters, that determine how a dial-up connection is to be handled. Specifically, the call policy parameters allow the selection of specific routers to which all user traffic should be directed. The call policy database may be configured in a number of ways, but

1 is preferably configured as a plurality of call policy records, each record defining a unique profile for a set of users requiring system access.

FIG. 11 is a schematic layout diagram of a call policy record 290 according to one embodiment of the present invention. The call policy record 290 includes a search key 291 for
5 keying-in to the record. The search key 291 may be designed to be one of various features or combination of features associated with an incoming call. Preferably, the search key 291 is a telephone number, an inlink or a channel within an inlink (e.g. DS0) on which the call is presented, or a combination of both. For example, if the search key indicates "called," the call policy is applied to the called phone number. If the search key indicates "calling," the call policy
10 is applied to the calling phone number. If the search key is "inlink," the call policy is applied to any calls received on a specified inlink. The specific inlink and/or channels is specified in a source link field 292 and/or source channel field 293. The called or calling phone numbers are specified in a phone number field 316.

Each call policy record 290 includes a call type 294 identifying a type of call received, and
15 a service type 296 identifying a type of service being requested by the call. According to one embodiment of the invention, the call type 294 includes ISDN and modem calls, and the service type 296 includes point-to-point protocol (PPP) or terminal services.

Each call policy record 290 further includes a QoS level 298 identifying the type of priority to be given to the call, and a QoS level 300 identifying the type priority to be given to the
20 packets to be conveyed once the call is accepted.

The call policy record 290 also includes a virtual router ID 302 and a virtual private network ID 304. The virtual router ID 302 identifies a virtual router to which the call is to be directed. As explained in further detail below, each virtual router is allocated a set of resources and routing protocols that allow the virtual router to act as an independent router within the
25 switch. The virtual private network ID 304 identifies a virtual private network that controls access to the virtual router.

In addition to the above, the call policy record 290 further specifies an authentication source 306 as being either the ISP's authentication server or a local database provided by the switch. If the authentication source is the ISP's authentication server, the call policy record
30 specifies a primary authentication server 312 and a secondary authentication server 314 that activates if the primary goes down.

The call policy record 290 also includes an IP address of a domain name server (DNS) to handle the call. The switch preferably supports a primary DNS address 308 and a secondary DNS address 310 that activates if the primary goes down.

35 In order to select the appropriate router for the dial-up connection, the call policy record 290 includes a domain ID 311 with an index to a domain database record. The domain database record includes the address of the router that is to handle the traffic originated from the user.

1 FIG. 12 is a process flow diagram for policy based routing according to one embodiment of the invention. The program starts, and in step 318, the connection manager 46 detects an incoming call and notifies the resource manager 38 that there is a call. In step 320, the resource manager 38 interrogates the call policy database and retrieves the appropriate call policy record
5 290 using one or more of the search keys 291. In step 322, the call parameters listed in the call policy record 290 are identified and applied in step 324. Other policies such as domain-based routing may also be applied if appropriate. In step 326, the program routes the call to the appropriate router based on the policy parameters.

10 IV. QUALITY OF ACCESS IN ACCESS SERVERS

10 Another feature of the multi-service network switch of FIG. 1 is the ability to allow tiered access to system resources including dial-in modem and ISDN resources by assigning QoA service levels to incoming connection requests. In this way, an ISP utilizing the switch may offer different access service levels with different pricing for each service level. The higher the QoA service level, the higher the access priority, and consequently, the higher the probability of getting
15 a connection when resource availability in the switch is low.

 According to one embodiment of the invention, the QoA level for an incoming connection is defined in the call policy record 290. The call policy record designates QoA access levels based on a particular feature of the incoming call, such as the type of inlink, phone number, and the like. When a connection is requested, the call's call policy record is retrieved and the call's
20 QoA level identified. A requested resource is then allocated to the call based on the identified QoA level and current resource usage.

 If the ISP's authentication server is used for authenticating the user, a QoA level for the user is further defined as part of the user configuration information. The QoA level in the authentication server may be configured to override the QoA level in the call policy record.

25 FIG. 13 is a schematic layout diagram of a QoA table 332 according to one embodiment of the invention. The QoA table 332 includes a default number of QoA levels 328 and access thresholds 330 associated with each QoA level. According to one embodiment of the invention, the default number of QoA levels 328 is four. The access threshold 330 associated with each QoA level 328 preferably indicates a maximum number of resources that may be in use before
30 a resource is allocated to the connection request. If the resource utilization exceeds the access threshold 330 corresponding to the user's QoA level 328, the request is refused. In the example of FIG. 13, a user with the lowest QoA level (level one) always has access to available system resources. A user with a QoA level of two has access to available system resources until 75 percent of those resources are in use. At that point, no new users in the same QoA level are
35 permitted access to system resources until more resources become available. For a user with a QoA level of four, system resources become limiting once the access threshold reaches 25 percent.

1 According to one embodiment of the invention, the system reserves the system resources
for other connections by disconnecting users with low QoA levels. In this regard, the resource
manager 38 periodically checks the utilization of system resources (e.g. every 60 seconds.) The
resource manager 38 compares the system resources in use to the access threshold 330 associated
5 with each logged-in user's QoA level. If the system resources in use exceed a user's access
threshold 330, the user is disconnected. If multiple users with different QoA levels are connected
to the Internet, the resource manager 38 preferably disconnects users in descending order. For
example, level four QoA users are disconnected first, then level three QoA users, and so on, until
enough resources have been reclaimed to serve future connection requests.

10 For example, assume that three users are connected to the Internet. User 1 has QoA level
of one, User 2 has a QoA level of two, and User 3 has a QoA level of three. If system resource
usage is 50 percent or less, all three users remain connected to the switch. If system resource
usage reaches 70 percent, only User 1 and User 2 remain connected. User 3 is disconnected and
the resources that were consumed by User 3 are reclaimed by the resource manager 38. If the
15 system resource usage reaches 80 percent or higher, only User 1 remains connected.

When multiple users with the same QoA level are connected to the Internet, the resource
manager 38 preferably disconnects the users within the same level in a first-in-first-out manner.
Thus, the user that has been logged on the longest is disconnected first.

V. MODEM POOL MANAGEMENT FOR DIAL APPLICATIONS

20 Another feature of the multi-service network switch of FIG. 1 is the ability to dynamically
allocate system resources to incoming connection requests. Resources are not tied to specific
ports, but may be shared among the various cards on a needed basis.

FIG. 14 illustrates the path that a connection might take if resources are being shared. In
the example of FIG. 14, the connection is a modem call that arrives as a DS0 on one port of a T1
25 WAN line interface FM 380. The FM has no modems of its own, so the resource manager 38
locates an available modem and routes the DS0 over the TDM bus 18 to the digital modem server
FM 382. After demodulation, the resulting packets are processed as appropriate and forwarded
over the cell bus 20 to an output FM 384.

30 According to one embodiment of the invention, the resource manager 38 resident in each
FM 10 is responsible for allocation and management of system resources. The resource manager
preferably keeps a table of local resources and broadcasts this information to all other FMs 10
in the system. Each FM 10 then has a complete view of the total resources available or in use
in the switch. The resource manager 38 is also preferably responsible for monitoring the health
of local resources. For example, suspect modems may be marked as being unavailable and put
35 out-of-service.

FIG. 15 is a schematic layout diagram of a modem resource table 334 maintained by the
resource manager 38 according to one embodiment of the invention. Similar tables are also
preferably maintained for ISDN and other system resources.

1 The resource manager 38 tracks available modem resources in the modem resource table 334 by both QoA level and virtual router (VR). Thus, the table 334 includes a VR ID field 336 identifying the virtual router for whom modem resources are being tracked. A maximum local resources field 338 indicates a maximum number of modems allocated to the VR on the FM 10. 5 A value of zero for this field may indicate that the FM 10 is not a modem module. A maximum global resources field 340 indicates a maximum number of modems on the entire switch that have been allocated to the VR.

10 A current local resources field 342 indicates a current number of modems available to the VR on the FM 10. The difference between this number and the number from the maximum local resources field 338 indicates the number of modems in use by the VR on the FM 10. A current global resources field 344 indicates that the number of modems in use by the VR on the entire switch. The difference between this number and the number from the maximum global resources field 340 indicates the number of modems in use by the VR on the entire switch.

15 A QoA field 346 indicates the QoA levels supported by the switch. According to one embodiment of the invention, the switch supports four QoA levels, with level one being of highest priority.

20 A local QoA field 348 indicates the number of modems available in the FM 10 for the listed QoA class for the VR indicated. In the example of FIG. 15, level one QoA accesses the switch when there are zero or more modems available (100% of the time), level two QoA accesses the shelf when there are 8 or more modems available (75% of the time), level three QoA accesses the switch when there are 16 or more modems available (50% of the time), and level four QoA accesses the switch when there are 24 or more modems available (25% of the time).

25 A global QoA field 350 provides similar information as the local QoA field 348, but for the entire switch. Thus, the global QoA field 350 indicates the number of modems available in the entire switch for the listed QoA class for the VR indicated.

30 An accept local field 352 indicates whether each of the listed QoA levels may access the FM 10 based on the number of local resources available as indicated by the current local resources field 342. The valid values are preferably yes and no. The yes and no values are calculated dynamically so that as resources are consumed, the yes values may change to no values, with the exception of the level one QoA, which always is allowed access.

35 An accept global field 354 provides similar information as the accept local field 352, but for the entire switch. Thus, the accept global field 354 indicates whether each of the listed QoA levels may access the switch based on the number of global resources available as indicated by the current global resources field 344.

FIG. 16 is a flow diagram of a resource allocation process according to one embodiment of the invention. When a user initiates a connection request in step 356, the connection manager 46 detects the incoming connection request in step 358 via one of the interface lines, and in step

1 360, notifies the resource manager 38 residing in the FM 10 receiving the request (the receiving FM). In step 362, the resource manager 38 retrieves the appropriate call policy record 290 from the call policy database based on the characteristics of the connection request. The retrieved call policy record includes, among other things, the type of call, QoA level and the VR ID associated with the call.

5 Based on the type of call, the resource manager 38 determines the type of resource to allocate to the call. For instance, if the call is an ISDN call, ISDN resources are allocated. On the other hand, if the call is a modem call, modem resources are allocated.

10 In step 364, the program inquires whether the identified resource resides locally in the receiving FM 10. If the answer is YES, the resource manager 38, in step 366, allocates the identified resource to the call based on the identified VR ID and QoA level. In step 368, the resource manager 38 proceeds to update its local resource table 334 indicating the allocation of the identified resource. Furthermore, the resource manager 38 in the receiving FM 10 transmits a broadcast message indicating that the identified resource has been allocated, allowing each of the other resource managers to also update their respective resource tables. In step 370, the user is authenticated, preferably via the ISP's authentication server, and may now start transmitting and receiving data packets.

20 Referring back to step 364, if the identified resource does not exist locally, the resource manager 38 broadcasts, in step 372, a resource request including the QoA level and VR ID associated with the incoming call. The resource managers 38 in the other FMs 10 receive the request and examine their local resource tables 334 for determining if there is a resource available for the specified QoA level and VR ID. If there is, the receiving FM 10, in step 374, receives a messages from each FM 10 indicating availability of the requested resource. According to one embodiment of the invention, the first FM 10 to respond to the connection request is assigned the call, and the other responses are ignored.

25 In allocating the resource to the call, as reflected in step 366, the connection manager 46 of the receiving FM 10 broadcasts a connection request to connect to the resource in the first responding FM 10. The connection manager 46 in the responding FM 10 then responds with a message that the call has been connected. According to one embodiment of the invention, the responding FM 10 allocates a modem from its local pool starting sequentially with the modem on port one. The next call the responding FM 10 takes goes to port 2, then port 3, and so on. If a call is hung up on port 1 or port 2 before port 3 takes a call, ports 1 and 2 remain idle, and the third call is still allocated to port 3. If a modem port is in use and this port is the next one that would normally answer the call, the allocation of the port becomes randomized and any subsequent port may answer the call.

35 If there are no resources available that match the specified QoA and VR ID, the connection manager 46 in the receiving FM 10 causes the call to be terminated.

1 If a call has been connected and allocated a resource, and if the call is to be terminated, the interface line transmitting the call receives a request to disconnect the call, and it informs the connection manager 46. If the call has been allocated a local resource from the receiving FM 10, the call is locally terminated and the resource allocated to the call is returned to the free pool.
5 All resource managers 38 then update their resource tables to reflect that the resource has become available.

 If the call has been allocated a resource from a different card, the connection manager 46 in the receiving FM 10 broadcasts a request to disconnect the resource. The connection manager 46 in the FM 10 that allocated the resource then proceeds to disconnect the call. The connection
10 manager 46 in the FM 10 that allocated the resource then broadcasts a message informing that the call has been disconnected. The resource is then returned to the free pool and the resource manager on each FM 10 updates their resource tables to reflect that the resource has become available.

VI. MULTIPLE VIRTUAL ROUTERS

15 Another feature of the multi-service network switch of FIG. 1 is the ability to partition the switch into multiple virtual routers (VRs) where each VR has allocated to it a set of resources (e.g. ISDN or modem resources) and routing tables. Thus, each VR functions as a separate router in an independent and self-contained manner.

 The system's approach to resource management enables the efficient provisioning of VRs.
20 As described above, system resources are not tied to a particular slot or interface, allowing them to be flexibly partitioned among the various VRs.

 According to one embodiment of the invention, a default system router is created at system boot-up. This router is preferably always present in the system, and all resources initially belong to the system router until they are reassigned to the VRs.

25 A system administrator may create new VRs and assign resources to the VRs. The system administrator may also perform routing configurations for the VRs.

 A new VR is preferably created by assigning it a unique name and a unique VR ID. The new VR is then configured by setting-up its physical interfaces, IP interfaces, and enabling its routing protocols. Once configured, the VR is then enabled and may thus function as an
30 independent router.

 Specifically, a portion of the resources available to the system are allocated to the newly created VR. Such resources may include dial modem, ISDN, T1, PRI, Ethernet, and/or frame relay resources. Ethernet resources are partitioned on a per PM basis. Thus, each VR either has the entire Ethernet switch PM 12a or none at all. PRI and T1 resources are partitioned at the DS0
35 level. Frame relay resources are partitioned at the PVC (permanent virtual circuit) level.

 Each VR is also allocated a number of modem and ISDN resources in the dial-up pool. According to one embodiment of the invention, each VR is allocated some fixed percentage or some fixed number of the pool. The resource manager 38 monitors the usage of the resources

1 for each VR for each QoA level. When a call is received, the resource manager 38 identifies the VR ID of the incoming call and dynamically allocates the modem or ISDN resources if it is within the limits set for the VR and the user's QoA.

5 In addition, each VR has an instance of an IP protocol stack and its own routing table 70 for routing protocols including RIP, OSPF, GBP4, and the like. The SCM 14 thus maintains a routing table 70 for each VR according to the VR ID as is illustrated in FIG. 17. In addition, each VR has its own forwarding table 90 and IP cache 102 for forwarding IP packets which are also maintained based on the VR ID.

10 Each VR may further be partitioned into multiple virtual private networks (VPNs) for controlling access to certain portions of the VR. Access is controlled by filtering software that filters traffic directed to the VR based on criteria such as source and/or destination addresses.

15 According to one embodiment of the invention, VPNs consist of VPN sessions, VPN rules, and VPN filters. VPN sessions are a set of criteria that the switch compares against traffic in the network. VPN rules determine how the packets that match the VPN session are to be processed. VPN filters bind VPN sessions to VPN rules.

20 FIG. 18 is a schematic layout diagram of a sessions table 240 including various VPN sessions according to one embodiment of the invention. Each VPN session of FIG. 18 includes a session ID 242 for classifying a particular session. Because sessions are consulted in numerical order, the session ID 242 also preferably indicates the order in which sessions in the sessions table 240 are compared to packets. For example, session 1 is compared first, then session 2, and so on. If a packet does not match one of the sessions, it proceeds through the list to the next session.

25 Each session preferably also includes a VPN ID 244 for classifying and categorizing dial-up connections. For instance, one group of users may constitute a company's employees with a specific VPN ID 244 who may be given access to the company's network as well as to the Internet, and a second group of users may constitute customers with a different VPN ID 244 who may be given access to the Internet, but not to the company's network. In one embodiment of the invention, each user's VPN ID is configured in the ISP's authentication server.

30 Each session also includes an IP source address 246 and destination address 250 pair to match against packets transmitted and received in the network. A source comparison mask 248 and a destination comparison mask 250 allow the specification of a subnet, a group of hosts, or all addresses. In this way, the switch identifies the packets that are candidates for the filtering process.

35 For example, a session ID 242 of "1," VPN ID 244 of "111," source address 246 of "any," source comparison mask 248 of "any," a destination address of "10.1.0.0," and a destination comparison mask 252 of "255.255.0.0" indicates a VPN session "1" for users with a VPN ID of "111" (e.g. company employees), and allows them to come from anywhere on any source address, and access any subnet on the 10.1.0.0 network (e.g. the company LAN). On the other hand, a

1 session ID 242 of "2," VPN ID 244 of "any," source comparison mask 248 of "255.255.0.0,"
destination address of "208.277.214.0," and destination comparison mask 252 of "255.255.255.0"
indicates a VPN session "2" for any user (VPN ID "any") on any subnet on the 10.1.0.0 network
(e.g. the company LAN) to access network 207.221.211.0 (e.g. the dial-up pool for accessing the
5 Internet). In these examples, packets are compared against each session in ascending numerical
order based on the session ID. Thus, if a packet does not match against session ID 242 "1," it is
then compared against session ID "2."

Once a packet is targeted for filtering, the VPN rules specify a set of conditions about how
the packet is to be processed. The rule may specify that the packet is to be forwarded, or that they
10 packet is to be dropped.

FIG. 19 is a schematic layout diagram of a rules table 254 including various VPN rules
according to one embodiment of the invention. Each VPN rule includes a rule ID 256 for
identifying the conditions in the rule. Each VPN rule also includes a rule priority 258 indicating
the order in which the rules are applied for a packet that matches a particular VPN session. An
15 action field 260 indicates the action that the rule is to perform on the packet. Valid actions
preferably include forwarding or dropping the packets.

Each session further includes an IP protocol field 262 and an application layer protocol
field 264. The IP protocol field indicates the name of the IP protocol that is to be filtered. The
application layer protocol field 264 indicates the application layer protocol that delivered the
20 packet to the VPN.

A session count field 266 indicates the number of VPN sessions that use the rule. A
packet count field 268 indicates the number of packets that are forwarded or dropped by the
switch.

The VPN filter is preferably the entity that binds a VPN session to a VPN rule. Thus,
25 when a packet is identified for filtering based on the criteria in the session table 240, the software
consults the rule associated with the session from the rules table 254, and the rule determines
whether the packet proceeds through the network.

FIG. 20 is a schematic layout diagram of a filter table 270 including various VPN filters
according to one embodiment of the invention. Each filter includes a session 272 and a rule 274
30 that is bound to the session 272. The session 272 corresponds to the session ID 242 in the
session table 240, and the rule 274 corresponds to the rule ID 256 in the rules table 254.

When a media port receives a packet, it determines whether it needs to be filtered. If so,
it is passed to a filtering module for carrying-out the appropriate filtering process. According to
one embodiment of the invention, the filtering module resides in each FM 10.

35 FIG. 21 is a flow diagram of a packet filtering process engaged by the filtering module
according to one embodiment of the invention. Each packet to be filtered includes a VPN ID.
Thus, the program starts, and in step 280 locates the VPN ID in the packet. The program also
searches the sessions table 240 for the appropriate VPN ID 244. The program searches the

1 sessions table 240 in ascending numerical order based on the session ID 242. Once the program
locates a session matching the VPN ID, the program, in step 282, inquires whether the packet's
source address matches the source address 246 specified for the session. If the answer is YES,
the program inquires in step 284 whether the packet's destination address matches the destination
5 address 250 specified for the session. If the answer is again YES, the program, in step 286,
searches the filter table 270 for the rule corresponding to the matched session. In step 288, the
program searches the rules table 254 for determining the conditions specified for the rule, and
processes the packet (i.e. forwards or drops the packet) based on these conditions.

VII. AUTOMATIC PROTECTION SWITCHING

10 Another feature of the multi-service network switch of FIG. 1 is its ability to provide fault
tolerance through automatic protection switching (APS) hardware and software. APS allows
component failures within the switch (e.g. terminating equipment failures) and external link
failures to be isolated and service be restored via backup components. Thus, if a terminating
equipment or an external link goes down, each is automatically rerouted to a backup component
15 without interruption in service. There are two elements to a connection, an external link and
a terminating equipment connecting to the external link. Thus, APS is preferably divided into
two areas, one area dealing with fault isolation and automatic recovery for terminal equipment
failures, and the other area dealing with fault isolation and automatic recovery for external link
failures.

20 The switch preferably supports any combination of primary and backup components. For
example, the backup may be a port on the same module (card), another module within the same
shelf, another module in a different shelf but within the same rack, or another module in another
shelf in another rack.

FIG. 22 is a schematic block diagram of a switch incorporating an APS mechanism for
25 external link failures. The switch includes a primary module 506 and a backup module 508
where the primary module accepts a primary WAN link 502 and the backup module accepts a
backup WAN link 504. Both the primary and backup modules include surge protection
equipment 510, 514, and a line interface unit (LIU)/framer 512, 518. The same data received by
the primary WAN link 502 is also preferably received by the secondary WAN link 504. If
30 software detects errors on the primary WAN link 502, such as transmission errors, the APS
software shifts the reading from the primary WAN link to the backup link 504. The shift from
the primary WAN link to the backup link is preferably instantaneous, without creating any
interruption to system functionality.

35 According to one embodiment of the invention, the backup WAN link 504 is selected from
a redundant port list (RPL). The redundant port list provides a user-defined list of backup links
for each link in the system. The backup link may be of the same type or different type than the
primary. For example, an ISDN connection could have a fractional-T1 link as a backup.

1 The switch further provides an APS mechanism for terminal equipment failures such as
faulty modules or faulty ports. According to one embodiment of the invention, there are two
ways for protecting terminal equipment. One way is having two or more ports in a card, where
each primary port is protected by a backup port. Thus, when a primary port goes down, a backup
5 port takes over. Another way involves having two or more cards, where each primary card is
protected by a backup card. Thus, when one card goes down, the other card takes over and
processes the data.

FIG. 23 is a schematic block diagram of a switch incorporating a backup port that is
physically connected to another port on a separate card. A primary module 501 includes a
10 primary port 503 and a backup port 505. The backup port 505 is physically connected to another
port 509 on a backup module 507 via a backup link 511. When a fault is detected on the primary
port 503, the relay diverts traffic to the backup port 505 which in turn directs the traffic to the
port 509 on the backup module 507.

According to one embodiment of the invention, a fault on the primary port 503 is detected
15 via hardware by monitoring the activity of the port. If there is no activity (e.g. no change) on the
port after a programmed period of time (e.g. 290 milliseconds), the protection relay 520
automatically switches to the backup port 505. The APS software keeps the data in the backup
port 505 up-to-date with the primary port. Thus, when there is a switch from the primary port
to the backup port, no loss of data is contemplated. If the backup port is on the same card, then
20 the same memory is used. If the backup port is on a different backup card, the APS software
preferably writes the data to both cards at the same time.

The APS architecture is preferably a 1:n architecture where each backup component
supports n primary components, where n is greater or equal to one. For example, a 1:2 protection
switching indicates that one backup component exists for every two primary components.
25 According to one embodiment of the invention, the switch offers a choice of 1:1, 1:2, 1:3, and
1:4 protection switching for T1/E1 links, and a choice of 1:1 and 1:2 protection switching for
CT3 links (E3, T3, and channelized OC3).

FIG. 24 is a schematic block diagram of a switch
incorporating a 1:2 protection switching according to one embodiment of the invention. Port
number one 522 and port number two 524 are both connected to a common backup port 526.
30 Port number one 522 is connected to the backup port 526 via backup link 528, and port number
two is connected to the backup port via backup link 530. Such 1:2 protection switching enables
either of the two working links to be switched to the protection circuitry.

FIG. 25 is a schematic block diagram of a switch incorporating a 1:2 protection switching
according to an alternative embodiment of the present invention. Port 1 has a first primary
35 connection 540 and port 2 has a second primary connection 542. Instead of each port having its
own backup connection, like in the embodiment of FIG. 25, both port 1 and port 2 share a backup
connection 544.

1 FIG. 26 is a schematic block diagram of another embodiment incorporating a 1:1 protection switching. External link B 532 acts as a backup for external link A 534. According to this embodiment, LIU and other logic is switched to either port A 538 or port B 540 via a selection relay 536. Thus, if external link A 534 goes down, the relay 536 switches to port B 540
5 for reading data from the external link B 532.

VIII. MODULAR, INDEPENDENT PROTOCOL STACK ARCHITECTURE

 Another feature of the multi-service network switch of FIG. 1 is its ability to support an IP routing protocol and architecture in which the layer two protocols are independent of the physical interfaces they run on. In contrast to known switch technology that attaches a protocol
10 to a physical port at compile time, the switch preferably configures a port with the appropriate protocol when the port is activated, that is, dynamically after a connection is made, allowing switch applications to be independent from the physical ports on which they run.

 The switch preferably supports a variety of wide area network (WAN) and local area network (LAN) physical interfaces. These physical interfaces include modem, ISDN, T1 and
15 fractional T1 (T1/FT1), unchannelized T3 (UT3), ATM OC3, ATM DS3, and Ethernet. The switch also supports a variety of layer two protocols including point-to-point protocol (PPP), PPP over frame relay (PPP/FR), PPP over Ethernet (PPOE), layer two tunneling protocol (L2TP), layer two forwarding (L2F), RFC 1483 Bridged, RFC 1483 Routed, RFC 1490 Bridged, and RFC 1490.

20 With the flexibility to dynamically configure a port, a single port may support an L2TP for one session and a L2F for another session. In addition, the same protocol may be run on different ports for each session. For instance, PPP typically comes over modem. However, with dynamic configuration of ports, PPP may also be run over Ethernet, T1, or ISDN lines, without being restricted to a single type of physical interface. Furthermore, the switch is not only capable
25 of processing different types of packets from different types of media, but is also capable of forwarding the packets to any kind of media. For example, data can come into the switch via PPP and go out over ATM.

 The dynamic configuration of ports may further be extended to a variety of media, such as narrow band for voice, broadband and DSL, to name a few. A port can also be dedicated such
30 as for T1. The software architecture enables modules for disparate media to communicate with one another all in one switch.

 FIG. 27 is a schematic block diagram of an IP forwarding layer 600, layer two protocols 602, and layer one physical interfaces 604. The dynamic configuration of ports allows, for example, PPP to be bonded to modem, ISDN, T1, UT3, ATM DS3, and ATM OC3. In addition,
35 layer two protocols 602 may be dynamically linked together to create a new layer two protocol. The new layer two protocol may then be bonded to a layer one interface 604.

 According to one embodiment of the invention, the port interface (PIF) 122 (FIG. 4) enables dynamic bonding of layer two protocols to layer one protocols. When a media port

1 becomes active, the switch creates a PIF object for the port. Preferably, PIFs are created by the-
GFI 124 (FIG. 4) software, triggered by the media driver 118. The PIF object determines the
layer two protocol to be utilized for the current session based on the type of connection, and the
GFI software dynamically bonds the layer two protocol to the layer one interface of the media
5 port. The protocol is linked for the duration of the session.

FIG. 28 is a schematic block diagram showing layer one, two, and three interfaces with
multiple PIFs 122, a PIF for every port. When a port is activated, the media driver 118 preferably
creates a PIF structure/module storing specific media and packet format information for the port
including port type, encapsulation, state information (e.g. active or inactive), and different port
10 numbers (e.g. physical port address, forwarding port address, and the back-plane port address).
The PIF also keeps track of the status of the PIF and reports changes to the FTAM, maintains
statistics of the ports, and maintains a pointer to the currently dialed-in user for dial-up ports.

According to one embodiment of the invention, the PIF structures are maintained as two
dimensional arrays using the controller number and the port number as the index. In order to
15 locate a particular PIF of a port, both the controller number and the port number within that
controller are used.

The PIFs for all the physical ports are preferably created when the card comes up. The
PIFs are initially in an inactive state. As the ports become active the PIF states are changed to an
active state. For dial-in ports, the PIF is put into an active state when a user dials in through that
20 port. When the call is disconnected, the PIF is put into an inactive state. The PIF is preferably
not removed because the PIF structure also keeps the port statistics and it is useful to keep the
port statistics even after the user is disconnected.

A port up message is sent by all the LAN cards to the SCM whenever a port changes its
state from an inactive state to an active state. The WAN cards do not normally send the port up
25 message to the SCM. The port up message is preferably sent by a WAN port if that port is
configured to carry the routing protocol update messages like RIP and OSPF packets.

A port down message is sent to all the cards in the chassis whenever a port's state changes
from an active state to an inactive state. The cards, after receiving this message, remove the
entries in the forwarding table and ARP table which refer to the port as being down.

30 The PIF module on the SCM is also responsible for maintaining and managing the RPL.
For each of the physical ports, the user can set up another physical port as the backup port. The
backup port is preferably not be part of any LPI. The backup port is used when the primary port
goes down. All the packets are normally sent to the primary port. The backup port is held in a
disabled state. Packets are neither received nor transmitted from the backup port when the
35 primary port is active. When the primary port goes down, the PIF module on the SCM enables
the backup port and all the packets from then on are sent on to the backup port. According to one
embodiment of the invention, when the primary port comes up again, the backup port is again
put into disabled state and all the packets again are sent to the primary port. Alternatively, the

1 packets continue using the backup port for the remainder of the session and do not switch to the primary port.

5 In an alternative embodiment of the invention, the RPL is maintained in a distributed manner. The RPL is distributed by the SCM to each card when the card comes up as part of its initialization. Each of the cards maintain the backup port in the disabled state. When the primary port goes down, an RPL port down message is sent to all the cards. When the cards receive the RPL port down message, each card searches its RPL table and for determining whether one of their ports is the backup port. If it is, then that card puts the port into an enabled state and starts handling traffic on that port. Also, all the cards remove all the entries in the forwarding table and
10 ARP table which refer to the primary port. From then on, all the traffic starts flowing onto the backup port. When the primary port comes back up, an RPL port up message is sent to all the cards. The card which has the backup port puts the port into a disabled state and sends a port down message for the backup port to all the cards. The port down message causes all the cards to remove the forwarding table and ARP table entries which refer to the backup port. From then
15 on, the primary port becomes active again. The RPL table is synchronized on all the cards. Whenever a change is made to the RPL table, it is distributed to all the cards by the SCM.

The IP Forwarder 44 (FIG. 4) interfaces to the PIF object and sends and receives packets to/from the PIF via the logical port identifier (LPI) 128. A logical port identifier (LPI) 128 communicates with the PIF 122 and includes the IP parameters related to each physical port. The
20 IP layer calls an LPI transmit function whenever it wants to transmit a packet. The LPI transmit function identifies the appropriate physical port and passes the packet to the PIF 122 for adding the media specific layer two encapsulation headers and transmitting it out the appropriate port.

After the initial packet has been processed, the identified layer two encapsulation headers
25 are preferably stored in an IP cache entry. This allows the IP Forwarder to bypass the PIF and Layer two functions for subsequent packets, minimizing packet processing overhead. Thus, for all subsequent packets, layer two encapsulation headers are taken from the IP cache entry.

IX. GENERIC FORWARDING INTERFACE

Another feature of the multi-service network switch of FIG.
30 1 is the ability to provide a uniform interface to the forwarding functions to mask the details of transmitting and receiving packets over different interface types. This is preferably done via the generic forwarding interface (GFI) 122 (FIG. 4) that enables applications (e.g. IP forwarder, PPP, and other functions provided by the switch) to send and receive packets in a generic
35 format.

According to one embodiment of the invention, GFI handles all internal packet forwarding, either between ports on the same

1 FM 10 or across the bus to other FMs 10 in the switch. GFI-
preferably makes forwarding functions transparent regardless of
whether a packet is forwarded to a remote card or a local card.
Furthermore, forwarding functions are transparent regardless of
5 the ingress and egress ports used for the packet. For example,
an ingress port may be frame relay over ISDN and the associated
egress port may be switched to a frame relay circuit without
going through the IP forwarder module 44 (FIG. 4).

GFI 124 provides protocol transparency by dividing the
10 switch into drivers 620 and applications 610 as is illustrated
in FIG. 29. Applications 610 are preferably bonded to drivers
620 at run time. This allows applications and drivers to be
attached and detached dynamically, providing flexibility to the
port. This dynamic bonding also frees memory and processing
15 resources not needed for unused protocols.

Applications and drivers desiring to receive and forward
packets register various functions with the GFI, including
receiving functions, forwarding functions, and/or polling
functions. Drivers 620 preferably register their forwarding
20 functions for forwarding packets to a physical port. If a packet
is to be forwarded to a physical port, GFI invokes the forwarding
function that is registered by the driver of the port.

Applications 610 preferably register their receiving
functions with GFI to receive and process incoming packets.
25 Receiver functions are registered to service various types of
packets including packets that have been received through media
ports, packets that have been forwarded, and packets destined to
known internal ports. A protocol processing or forwarding
application such as PPP or IP forwarder typically registers with
30 GFI to receive and process packets received through the media
ports. Forwarded packets are processed by applications that
perform translation and encapsulation for a particular output
port. Receiver functions also register with GFI to handle
packets destined to known internal ports, such as a management
35 channel that is used to exchange external management information.

Both applications 610 and drivers 620 may register polling
functions with the GFI for periodic invocation. Polling functions
are often used to check the operation of the switch. In a

1 preferred embodiment of the invention, two levels of polling-
frequency may be specified: high and low. Preferably, foreground
functions such as packet processing preferably uses high
5 processes use low frequency polling. In alternative embodiments
of the invention, multiple levels of polling frequency may be
used.

When a packet arrives into the system through a media port,
the packet is received by one or more buffers (GFI buffers) in
10 the shared memory 24 (FIG. 2). The driver associated with the
media port receives the packet and translates it into a generic
format using GFI utilities. The driver also builds a GFI
descriptor that defines the packet, and has pointers to buffers
that belong to the packet. The packet is then passed onto the
15 system for processing by the applications.

When a packet is to be transmitted to a physical port, GFI
invokes the appropriate driver's forwarding function to transmit
the packet. The driver's forwarding function is preferably
responsible for translating the generic packet into the driver's
20 specific format and transmitting it out the required port.

All packets introduced into the system are preferably
converted to a generic packet format (GPF) for protocol
transparency. FIG. 30 is a schematic block diagram of a GPF 700
according to one embodiment of the invention. The GPF 700
25 preferably includes a list of shared memory buffers and a
descriptor that points to the buffers. The descriptor is divided
into a general packet descriptor (GPD) 702 and one or more buffer
descriptors 704. The GPD preferably includes four words. In one
embodiment, the first word of the GPD includes a total byte count
30 706 for the packet as well as various routing flags 708. The
routing flags include flags for fragmentation, multicast,
switched, and monitored. In this embodiment, the total byte
count is the length of a packet.

The second word defines a QoS value 710 and VPN ID 712. The
35 VPN ID identifies a virtual private network associated with the
packet. The QoS value identifies the level of priority for
processing the packet. In a preferred embodiment of the
invention, GFI provides eight levels of QoS. Once a packet is

1 assigned a QoS value, GFI ensures that the packet is serviced-
throughout the system based on its QoS. GFI also allocates
resources such as CPU, backplane, communication channel, and
system buffers to the packets based on their QoS values.

5 The third word specifies an output port information 714.
The output port information is preferably filled in after the
packet's routing information has been determined from a lookup
in the IP forwarder module 44.

The fourth word identifies an input port 716 receiving the
10 packet. The fourth word also includes a reference count for
multicasting. The reference count is used by drivers to keep
track of a packet that is being transmitted to multiple ports.

The buffer descriptor preferably includes a buffer control
word and a pointer to a system buffer 717. The buffer control
15 word includes control information 718 as well as the number of
bytes of data 720 in the buffer. The control information
includes control flags that define the type of buffer.

A port addressing scheme used for the input port 714 and
output port information 716 enables forwarding of packets
20 anywhere in the switch. The port addressing scheme is preferably
hierarchical and it is based on chassis, cards, controllers, and
ports. Moreover, ports are divided into five categories: local
ports, internal multicast ports, internal unicast ports, external
multicast ports, and remote ports. According to one embodiment
25 of the invention, GFI provides two different types of port
addressing schemes, a forwarding port address (FPA) and a
physical port address (PPA). FIG. 31 is a schematic layout
diagram of an FPA according to one embodiment of the invention.
FPA is preferably used for forwarding packets throughout the
30 switch. FIG. 32 is a schematic layout diagram of a PPA
according to one embodiment of the invention. The PPA is
preferably used for external use, for administrative purposes,
and for configuring ports within a switch.

GFI preferably provides two types of FPA, a local FPA and a
35 backplane FPA. The local FPA is used to direct packets to local
media drivers. The backplane FPA is used to direct packets to
remote ports

1 Forwarding of packets is based on controller number for both-
local FPA and backplane FPA. Every device on the card preferably
has a controller number 601. For example, there is an Ethernet
controller for an Ethernet device and there is an ISDN controller
5 for an ISDN device. The controller number is part of the FPA.
The controller number allows the GFI to dispatch the packet to
the appropriate driver. According to one embodiment of the
invention, the controller number has local significance only.
If there are four drivers on one card, then there are four
10 different controller numbers allocated to the four drivers so
that the GFI can dispatch packets to them.

There is also a controller for the backplane driver. The
backplane driver preferably uses controller number zero. The
backplane is another driver that runs under the GFI. Backplane
15 packets do not go out of the switch. They go to another card in
the switch. All the packets which are to be forwarded to other
cards within the switch are sent to the backplane driver. If a
packet has to go to another card, then the controller number is
changed, allowing the packet to be sent to a remote port. The
20 scheme includes address ranges that determine the type of port.

The backplane also includes an address range. When sending
a packet from one card to another card such as a packet coming
into the switch from a modem and going to another card in frame
relay, the packet is redirected to the backplane by changing the
25 controller number to zero. Packets directed to remote ports are
directed to the backplane driver. When the packet is received at
the other card, the controller address is switched to frame
relay.

When a driver receives a packet from a port, it constructs a GPD 702 for the packet. In
30 doing so, the driver preferably constructs the input port 716 information as illustrated in FIG. 33.
The input port 716 information includes 8 flag bits and 24 address bits. The flag bits specify
source control information that permits the receiving application to apply appropriate routing and
encapsulation.

The output port information 714 is preferably built after the packet's routing information
35 is obtained from the forwarding module 44. FIG. 34 is a schematic layout
diagram of the output port information according to one
embodiment of the invention. The output port information 714
includes 8 flag bits and 24 address bits. The 8-bit flag field

1 is used as control information that is passed from the-
application to the drivers that is responsible for transmitting
the packet.

5 The output port information is preferably designed so that
applications can send a packet to a local port address (LPA),
known internal multicast (WKIM) address, known internal unicast
(WKIU) address, known external multicast (WKEM) address, dynamic
external multicast (DEM) address, and remote port address (RPA).

10 If a packet is being forwarded to a local port (i.e. local
to the card), the output port specifies the physical port address
as illustrated in FIG. 32. Local ports that are visible to the
other cards are mapped to backplane driver ports. The backplane
driver ports are used to direct packets to remote ports. The
backplane driver maps port addresses in the incoming packets to
15 local port addresses.

WKIM addresses provide internal communication paths between
applications on various modules. For example, if an application
running on the ISDN module wants to send a message to the
management IP stack running on the SCM, it uses the appropriate
20 WKIM address assigned to the SCM's IP stack. In the case where
there are multiple SCMs in the system, the message is sent to the
IP management stack of all the SCMs. If the user wants to
address a known internal port within a card, then the WKIU is be
used.

25 A WKEM is used to group a host of external ports together.
For example, a WKEM is setup for any application, such as OSPF,
that requires broadcasting to a list of ports. A DEM capability
allows the user to create and destroy multicast groups on the
fly.

30 If an application on one card wants to send a packet to an
external port on another card, it uses the RPA assigned to that
port. Before a remote port can be addressed there is a mapping
of the RPA to a physical port address. Each card in the system
is responsible for mapping its own physical ports to RPAs. In
35 the preferred embodiment of the invention, utilities in a header
file performs the required mapping.

With the exception of the local port address, all of the
above categories of addresses are preferably virtual addresses.

1 A virtual port address maps to one or more physical port-
addresses. The virtual address port assignments according to one
embodiment of the invention are illustrated FIG. 35. Preferably, controller number
0 is assigned to the virtual addresses. In a preferred embodiment of the invention, the backplane
5 address ranges are as follows:

	0	Reserved for Known internal management	channel
	1-7167	Dynamic port range (remote port address)	
	7168-7368	Known internal unicast ports	
10	7369-7568	Known internal multicast ports	
	7569-7668	Known external multicast ports	
	7669-8191	Dynamic multicast ports	

15 The known internal multicast is used to direct packets to
the internal applications that run on multiple cards. Examples
include OSPF, RIP, and call log. Known external multicast is
used to direct packets to a group of ports for a known
application. Examples are ports used by routing protocols such
as OSPF, RIP, and BGP4. Dynamic multicast is used by application
20 protocols that require dynamic creation and deletion of multicast
groups. In a dynamic multicast, members can be added and deleted
dynamically. IP multicast is one example of a dynamic multicast.

Another function provided by GFI is distributed
multicasting. To send a packet to a multicast group, only one
25 packet is created. When the packet is sent to a multicast group,
the packet is sent to the backplane. Then, the packet is
propagated to the multicast group. When recipients get the
packet, it gets propagated in the recipient card to the
appropriate media ports without having to copy the packet.

30 GFI further provides hardware configuration transparency.
For example, the number of CPUs and the DMA capability is
transparent to the applications. The memory layout between
platforms can be completely different from card to card. The GFI
makes it transparent to applications. Therefore, applications are
35 not concerned with drivers and memory. The specifics of a board
is determined at run time. The GFI moves all data structures
into the appropriate places based on the GFI's configuration.
When GFI is activated, it calls a generic platform function to

1 initialize the platform. The generic platform function gets the
parameters for a platform. The platform function detects what
kind of board/card it is and what type of memory it is and then
sets up the data structures and memory accordingly. Parameters
5 passed by the function determines shared memory configuration,
buffer size. For example, a parameter representing a modem
buffer size of 256k bytes may be passed back to the GFI. There
is a platform function for every card. Thus, the same code can
run on different cards.

10 The GFI software is designed to run on different hardware
platforms. For example, the GFI runs on all Personality Modules
as well as all Generic Hardware Modules (i.e. High Speed Generic
Module, Low Speed Generic Module, etc.). Once a driver is
implemented based on the GFI interface, it can move from platform
15 to platform without any modification. Moreover, the GFI makes
the CPU configuration (i.e. one CPU or two CPUs) of the system
transparent to the applications and drivers. No changes are
required to the drivers and applications when moving from a
single CPU configuration to a multiple CPU configuration, and
20 vice versa.

When processing packets in a single CPU platform, GFI goes
through a receive queue and checks the code set in the packet
descriptor. GFI further checks if there is any application
registered to receive the packet. The applications register with
25 the GFI at initialization time. If there is an application
registered to receive the packet, GFI invokes the application
that has been registered and gives the packet descriptor to the
application.

In a multiple CPU platform, there is a queuing CPU and an
30 application CPU. The queuing CPU does the queuing and the
application CPU does the processing. A macro puts the packet in
a QoS queue based on the QoS level that has been set in the
packet descriptor for the application CPU to process. The GFI
code makes the number of CPU configuration transparent. Whether
35 the GFI is running on one CPU or two CPUs, it does not matter to
the driver that invokes the GFI receive function. The GFI puts
a packet into a queue if running on a two CPU platform or it
invokes the function directly on a single CPU platform.

1 When a packet is passed to an application. The application can: (1) forward the packet; (2) drop the packet; or (3) hold the packet. When the application is called, it returns any of the above codes to the GFI.

5 One application is the IP forwarder module 44 who gets the IP packet and makes forwarding decisions regarding the packet. Once the forwarding decision is made, the IP forwarder module sets up the destination GFI address in the packet descriptor and returns a forward code. If the IP forwarder module determines
10 that the packet is not good or cannot be processed, then it returns a drop code to the GFI that the packet be dropped. If the IP forwarder module determines that the packet is to be held, the module transfers the packet later because the routing information has not yet been determined.

15 If the forward code is returned and the GFI is running on a dual CPU environment, the GFI queues the packet in the queuing CPU. If it is running on a single CPU, the GFI calls the dispatch function for GFI directly. The dispatch function decides based on which driver this packet has to go to and it
20 dispatches the packet to the appropriate transmit function to be sent out.

 When GFI runs on a two CPU platform, a set of queues are set up automatically, receive queues and forwarding queues. In one embodiment of the invention, there are 4 receive queues and 4
25 forwarding queues. Each queue is used to differentiate a different level of QoS. The GFI picks up the packet from the queue and processes it based on the QoS and then calls the dispatch function, then dispatches the packet for the appropriate driver transmit function. Which driver transmit function is
30 called depends upon the forwarding port address that is in the packet descriptor. The forwarding port address has a controller number and the controller number determines the driver that is to receive the packet.

 In an alternative embodiment of the invention, the GFI
35 supports 8 Receiving Queues (RQs) and 8 Forwarding Queues (FQs). FIG. 36 is a schematic layout diagram of the Receiving Queues and Forwarding Queues according to one embodiment of the invention. When the driver receives a packet, it uses the packet's assigned

1 QoS value to queue it to any of the 8 RQs. Similarly, when an
application is forwarding a packet, it uses the QOS value to
queue the packet to any of 8 FQs.

5 The above queuing scheme is preferably only used for the two
CPU configuration. When the GFI runs on a single CPU
configuration the forwarding and receiving queues are not created
or used. The GFI makes this transparent to the its users.

GFI further provides Inter-Processor Communication (IPC).
Using the IPC capability, applications running on different
10 processors on the same card can exchange messages. In order to
receive messages through the IPC an application registers with
the IPC using the function calls provided in the gfi-ipc.h. The
IPC provides two modes of operations: synchronous and
asynchronous. Using the synchronous mode, an application can send
15 a message to a client running on another CPU and wait for the
response. The IPC provides the mechanism for the responder to
send a message to the requester when the synchronous mode of
operation is used. If an application does not require explicit
acknowledgment of a message, then it uses the asynchronous mode
20 of operation. In this case, the IPC queues the message and
returns immediately back to the application.

Although this invention has been described in certain specific embodiments, many
additional modifications and variations would be apparent to those skilled in the art. It is
therefore to be understood that this invention may be practiced otherwise than as specifically
25 described. Thus, the present embodiments of the invention should be considered in all respects
as illustrative and not restrictive, the scope of the invention to be determined by the appended
claims and their equivalents.

30

35

1 CLAIMS:

1. A multi-service network switch for transferring blocks of data to a particular destination address, the switch comprising:

5 a plurality of interface modules, each interface module including a processor and a first memory for storing a forwarding table including a list of destination addresses and a known best route to each destination address;

a system control module including a second memory for storing a routing table including a list of destination addresses reachable by each of the interface modules and all known routes to each destination address, the routing table being referenced if the particular destination address is not found in the forwarding table; and

10 a bus interconnecting the interface modules and the system control module for transferring the blocks of data to the particular destination address.

15 2. The switch of claim 1 further comprising a cache of recently used destination addresses and their corresponding physical port identifiers.

3. The switch of claim 1, wherein the first memory further stores an address resolution table including a list of destination addresses and their corresponding physical port identifiers.

20 4. The switch of claim 3 further comprising means for obtaining a physical port identifier corresponding to the particular destination address if the particular destination address is not found in the address resolution table.

25 5. The switch of claim 1, wherein each interface module includes an interface line for receiving from a user a connection request, and the processor is operable to execute program instructions including:

identifying a characteristic of the connection request;

30 selecting a router based on the identified characteristic; and

forwarding a data block originated from the user to the selected router.

6. The switch of claim 5, wherein the characteristic is selected from the group consisting of a type of line interface, user login information, telephone number, source address of the data block, and destination address of the data block.

35 7. The switch of claim 5, wherein the program instructions further include retrieving call profile information based on the identified characteristic.

1 8. The switch of claim 7, wherein the call profile information includes an access level
to be assigned to the connection request, the access level being associated with an access
threshold indicative of a maximum number of system resources that may be in use before the
connection request is granted.

5 9. The switch of claim 7, wherein the call profile information includes a virtual router
identifier to be assigned to the connection request, the virtual router being allocated a portion of
the system resources.

10 10. The switch of claim 1, wherein each interface module includes an interface line for
receiving an incoming connection request, and the first memory further stores a list of resources
and information about availability of each of the resources, and the processor being operable to
execute program instructions including:

15 identifying a particular resource to be allocated to the connection request;
querying the list of resources for the particular resource; and
allocating the particular resource to the connection request if the particular resource is
identified as being available.

20 11. The switch of claim 10, wherein the list of resources is a list of resources local to
the interface module.

25 12. The switch of claim 10, wherein the program instructions further comprise:
communicating a request for the particular resource from an interface module receiving
the incoming connection request to remaining interface modules;
receiving a response indicating that the particular resource is available; and
communicating a request to allocate the identified resource.

30 13. The switch of claim 10, wherein the program instructions further include:
assigning an access level to the incoming connection request based on a characteristic of
the connection request, the access level being associated with an access threshold;
determining an amount of current usage for the particular resource; and
allocating the identified resource to the connection request if the amount of current usage
is less than the access threshold associated with the assigned access level.

35 14. The switch of claim 10, wherein the program instructions further include:
creating a plurality of virtual routers, each virtual router being allocated a plurality of
resources;
maintaining the list of resources according to the virtual routers;

1 identifying the virtual router associated with the connection request; and
allocating the identified resource to the connection request if the particular resource is
identified as being available for the identified virtual router.

5 15. The switch of claim 1 wherein each interface module includes a plurality of
resources, a portion of the resources being allocated to a virtual router, the switch further
comprising:

means for receiving a connection request directed to the virtual router;
means for assigning a resource to the connection request from the portion of resources
10 allocated to the virtual router;
means for receiving a block of data from the connection;
means for locating a filter associated with the block of data, the filter including a filtering
criteria and an action to be taken upon a match of the filtering criteria; and
means for processing the block of data based on the located filter.

15 16. The switch of claim 15, wherein the filtering criteria is selected from the group
consisting of a source address of the block of data and a destination address of the block of data.

20 17. The switch of claim 15, wherein the action to be taken is selected from the group
consisting of forwarding the block of data and dropping the block of data.

18. The switch of claim 1, wherein the interface modules further include:
a first input port receiving the blocks of data;
a second input port coupled to the first input port, the second input port acting as a backup
25 for the first input port;
means for detecting a failure on the first input port; and
a relay for automatically diverting the blocks of data from the first input port to the second
input port upon detection of failure on the first input port.

30 19. The switch of claim 18, wherein the first and second input ports reside in the same
interface module.

20. The switch of claim 18, wherein the first and second input ports reside in different
interface modules.

35 21. The switch of claim 1, wherein one of the interface modules includes a first input
port coupled to a first link and another one of the interface modules includes a second input port
coupled to a second link acting as a backup to the first link, wherein the blocks of data are

1 automatically diverted from the first link to the second link upon a detection of failure on the first link.

5 22. The switch of claim 21, wherein the second link is selected from a plurality of available links.

23. The switch of claim 1 further comprising:
an input port receiving a first packet in a first protocol;
an input driver coupled to the input port for translating the first packet into a generic
10 format;
means for passing the generic packet to an application;
means for receiving from the application the generic packet;
an output driver for translating the generic packet into a second protocol; and
an output port coupled to the output driver for transmitting out the translated packet.

15 24. The switch of claim 1, wherein the interface modules further include:
an input port for receiving a connection request;
means for identifying a protocol associated with the connection request; and
means for dynamically bonding the identified protocol to the input port.

20 25. The switch of claim 24, wherein the interface modules further include means for adding encapsulation information to the data blocks, the encapsulation information being associated with the identified protocol.

25 26. The switch of claim 25 further comprising a cache for storing the encapsulation information.

27. A multi-service network switch including a plurality of interface modules, each interface module comprising:
30 interface lines for receiving an incoming connection request;
a memory storing a list of resources and information about availability of each of the resources; and
a processor coupled to the memory, the processor being operable to execute program instructions including:
35 identifying a particular resource to be allocated to the connection request;
querying the list of resources for the particular resource; and
allocating the particular resource to the connection request if the particular resource is identified as being available.

1 28. The interface module of claim 27, wherein the list of resources is a list of resources
local to the interface module.

5 29. The interface module of claim 27 further comprising:
communicating a request for the particular resource from the receiving interface module
to remaining interface modules;
receiving a response indicating that the particular resource is available; and
communicating a request to allocate the identified resource.

10 30. The interface module of claim 27, wherein the program instructions further include:
assigning an access level to the incoming connection request based on a characteristic of
the connection request, the access level being associated with an access threshold;
determining an amount of current usage for the particular resource; and
15 allocating the identified resource to the connection request if the amount of current usage
is less than the access threshold associated with the assigned access level.

20 31. The interface module of claim 27, wherein the program instructions further
include:
creating a plurality of virtual routers, each virtual router being allocated a plurality of
resources;
maintaining the list of resources according to the virtual routers;
identifying the virtual router associated with the connection request; and
25 allocating the identified resource to the connection request if the particular resource is
identified as being available for the identified virtual router.

30 32. A multi-service network switch including a plurality of interface modules, each
interface module comprising:
interface lines for receiving an incoming connection request;
a memory storing a plurality of access levels, each access level being associated with an
access threshold; and
a processor coupled to the memory, the processor being operable to execute program
instructions including:
35 assigning an access level to the incoming connection request based on a
characteristic of the incoming connection request;
identifying the resource requested by the incoming connection request;
communicating a request for the identified resource, the communicated request
including the assigned quality of access level;
receiving a response indicating that the identified resource is available; and

1 communicating a request to allocate the identified resource.

33. The interface module of claim 32, wherein the program instructions further comprise:

5 monitoring usage of the local resources for each access level;
receiving the request for the identified resource;
determining an amount of current usage for the identified resource; and
allocating the identified resource to the incoming connection request if the amount of
current usage is less than the access threshold associated with the assigned access level.

10

34. The interface module of claim 32, wherein the local resources are partitioned among a plurality of virtual routers, and the memory stores the list of local resources for each virtual router.

15

35. The interface module of claim 32, wherein the characteristic is selected from the group consisting of a type of inlink carrying the incoming connection request, a telephone number associated with the incoming connection request, and a type of user submitting the connection request.

20

36. A multi-service network switch comprising:
an interface line for receiving from a user a connection request;
an interface module coupled to the interface line, the interface module including a processor operable to execute program instructions including:

25

identifying a characteristic of the connection request;
selecting a router based on the identified characteristic; and
forwarding a data block originated from the user to the selected router.

30

37. The switch of claim 36, wherein the characteristic is selected from the group consisting of a type of line interface, user login information, telephone number, source address of the data block, and destination address of the data block.

38. The switch of claim 36, wherein the program instructions further include retrieving call profile information based on the identified characteristic.

35

39. The switch of claim 38, wherein the call profile information includes an access level to be assigned to the connection request, the access level being associated with an access threshold indicative of a maximum number of system resources that may be in use before the connection request is granted.

1 40. The switch of claim 39, wherein the program instructions further include:
 identifying the resource requested by the connection request;
 determining an amount of current usage for the identified resource; and
 allocating the identified resource to the connection request if the amount of current usage
5 is less than the access threshold associated with the assigned access level.

 41. The switch of claim 38, wherein the call profile information includes a virtual
router identifier to be assigned to the connection request, the virtual router being allocated a
portion of the system resources.

10

 42. The switch of claim 41, wherein the interface module further includes a memory
coupled to the processor for maintaining a list of resources and information about availability of
each of the resources, and the program instructions further include:
 identifying a particular resource to be allocated to the connection request;
15 querying the list of resources for the particular resource; and
 allocating the particular resource to the connection request if the particular resource is
identified as being available.

 43. A multi-service network switch comprising:
20 a plurality of interface modules receiving and forwarding data blocks, each interface
module including a plurality of resources;
 means for creating a plurality of virtual routers, each virtual router being associated with
a unique virtual router identifier;
 means for allocating a portion of the resources to each virtual router, the allocated
25 resources being proprietary to each virtual router;
 means for monitoring usage of resources allocated to each virtual router;
 means for receiving a connection request;
 means for identifying the virtual router for the connection request;
 means for determining availability of resources allocated to the virtual router; and
30 means for assigning the resource to the connection request if the resource is available.

 44. The switch of claim 43, wherein the means for monitoring comprises means for
monitoring usage of resources allocated to each virtual router based on a quality of access level,
the quality of access level being associated with an access threshold indicative of a maximum
35 number of resources allowed to be in use before a resource is allocated to the connection request.

1 45. The switch of claim 43 further comprising means for creating for each virtual router a set of filters, each filter being associated with a filtering criteria and an action to be taken upon a match of the filtering criteria by a block of data directed to the virtual router.

5 46. A data switch including a plurality of interface modules, the switch comprising:
a first input port receiving a block of data;
a second input port coupled to the first input port, the second input port acting as a backup
for the first input port;
means for detecting a failure on the first input port; and
10 a relay for automatically diverting the block of data from the first input port to the second
input port upon detection of failure on the first input port.

15 47. The switch of claim 46, wherein the first and second input ports reside in the same
interface module.

15 48. The switch of claim 46, wherein the first and second input ports reside in different
interface modules.

20 49. The switch of claim 46, wherein the second input port acts as a backup for two or
more primary ports.

25 50. A data switch including a plurality of interface modules, the switch comprising:
a first interface module including a first input port coupled to a first link, the first input
port receiving a block of data;
a second interface module including a second input port coupled to a second link, the
second link acting as a backup to the first link;
means for detecting a failure on the first link; and
means for automatically switching receipt of data from the primary link to the backup link
upon detection of failure on the primary link.

30 51. The switch of claim 50, wherein the second link is selected from a plurality of
available links.

35 52. A switching system comprising:
an input port receiving a first packet in a first protocol;
an input driver coupled to the input port for translating the first packet into a generic
format;
means for passing the generic packet to an application;

1 means for receiving from the application the generic packet;
an output driver for translating the generic packet into a second protocol; and
an output port coupled to the output driver for transmitting out the translated packet.

5 53. The switching system of claim 52, wherein the input and output drivers register with a generic forwarding interface, the generic forwarding interface being located between the drivers and the application.

10 54. The switching system of claim 52 further comprising a receiving queue for receiving the generic packet, the receiving queue corresponding to a quality of service level of the generic packet.

15 55. The switching system of claim 52 further comprising a forwarding queue for receiving the generic packet from the application, the forwarding queue corresponding to a quality of service level of the generic packet.

20 56. A switching system comprising:
a plurality of drivers;
a plurality of applications;
a plurality of receiving queues each queue corresponding to quality of service level; and
the generic forwarding interface located between the plurality of drivers and the plurality of applications, wherein the generic forwarding interface places a packet from a driver into a receiving queue corresponding to the quality of service of the packet.

25 57. The switching system of claim 56 wherein the generic forwarding interface takes the packet out of the receiving queue and sends the packet to an application registered for the packet.

30 58. A data switch comprising:
an input port for receiving a connection request;
means for identifying a protocol associated with the connection request;
means for dynamically bonding the identified protocol to the input port;
means for receiving a data block from a layer three interface; and
means for adding encapsulation information to the data block, the encapsulation
35 information being associated with the identified protocol.

59. The switch of claim 58 further comprising a cache for storing the encapsulation information.

1 60. A data switch comprising:
means for establishing a first connection on a port;
means for creating a port interface (PIF) object for the port;
means for detecting a first protocol of the connection;
5 means for bonding the first protocol to the PIF;
means for receiving a data block on the port; and
means for forwarding the data block to a destination address.

10 61. The switch of claim 60 further comprising:
means for establishing a second connection on the port;
means for creating a second port interface (PIF) layer for the port;
means for detecting a second protocol of the connection;
means for bonding the second protocol to the second PIF;
means for receiving a second data block on the port; and
15 means for forwarding the second data block to a second destination address.

20 62. In a multi-service network switch including a plurality of interface modules and a
system control module, a method for forwarding data blocks to a destination address comprising:
storing in each interface module a forwarding table including a list of destination addresses
and a known best route to each destination address;
storing in the system control module a routing table including a list of destination
addresses reachable by each of the interface modules and all known routes to each destination
address reachable from the interface modules, the routing table being referenced if the particular
destination address is not found in the forwarding table;
25 receiving a block of data for forwarding to the particular destination address;
obtaining a route to the destination address; and
forwarding the data block to the particular destination address.

30 63. The method of claim 62 further comprising storing in a cache a list of recently used
destination addresses and corresponding physical port identifiers.

64. The method of claim 62 further comprising storing an address resolution table
including a list of destination addresses and their corresponding physical port identifiers.

35 65. The method of claim 64 further comprising obtaining a physical port identifier
corresponding to the particular destination address if the particular destination address is not
found in the address resolution table.

1 66. The method of claim 62 further comprising:
receiving from a user a connection request;
identifying a characteristic of the connection request;
selecting a router based on the identified characteristic; and
5 forwarding a data block originated from the user to the selected router.

67. The method of claim 66, wherein the characteristic is selected from the group consisting of a type of line interface, user login information, telephone number, source address of the data block, and destination address of the data block.

10 68. The method of claim 66 further comprising retrieving call profile information based on the identified characteristic.

69. The method of claim 68, wherein the call profile information includes an access level to be assigned to the connection request, the access level being associated with an access threshold indicative of a maximum number of system resources that may be in use before the connection request is granted.

70. The method of claim 68, wherein the call profile information includes a virtual router identifier to be assigned to the connection request, the virtual router being allocated a portion of the system resources.

71. The method of claim 62 further comprising:
maintaining in each interface module a list of resources and information about availability of each of the resources;
25 identifying a particular resource to be allocated to the connection request;
querying the list of resources for the particular resource; and
allocating the particular resource to the connection request if the particular resource is identified as being available.

30 72. The method of claim 71, wherein the list of resources is a list of resources local to the interface module.

73. The method of claim 71 further comprising:
communicating a request for the particular resource from an interface module receiving
35 the incoming connection request to remaining interface modules;
receiving a response indicating that the particular resource is available; and
communicating a request to allocate the identified resource.

1 74. The method of claim 71 further comprising:
 assigning an access level to the incoming connection request based on a characteristic of
the connection request, the access level being associated with an access threshold;
 determining an amount of current usage for the particular resource; and
5 allocating the identified resource to the connection request if the amount of current usage
is less than the access threshold associated with the assigned access level.

 75. The method of claim 71 further comprising:
 creating a plurality of virtual routers, each virtual router being allocated a plurality of
10 resources;
 maintaining the list of resources according to the virtual routers;
 identifying the virtual router associated with the connection request; and
 allocating the identified resource to the connection request if the particular resource is
identified as being available for the identified virtual router.

15 76. The method of claim 62 further comprising:
 receiving a connection request directed to the virtual router;
 assigning a resource to the connection request from the portion of resources allocated to
the virtual router;
20 receiving a block of data from the connection;
 locating a filter associated with the block of data, the filter including a filtering criteria and
an action to be taken upon a match of the filtering criteria; and
 processing the block of data based on the located filter.

25 77. The method of claim 76, wherein the filtering criteria is selected from the group
consisting of a source address of the block of data and a destination address of the block of data.

 78. The method of claim 76, wherein the action to be taken is selected from the group
consisting of forwarding the block of data and dropping the block of data.

30 79. The method of claim 62 further comprising:
 maintaining a backup port for each primary port coupled to the interface modules;
 receiving a block of data on the primary port;
 detecting a failure of the primary port; and
35 automatically diverting the block of data from the primary port to the backup port
associated with the primary port upon detecting the failure.

1 80. The method of claim 79, wherein the backup port resides on the same interface module as the primary port.

5 81. The method of claim 79, wherein the backup port resides on a different interface module as the primary port.

 82. The method of claim 79, wherein two or more primary ports are associated with the same backup port.

10 83. The method of claim 62 further comprising:
 maintaining a backup link for each primary link coupled to the interface modules;
 receiving a block of data on the primary link;
 detecting a failure of the primary link; and
 automatically switching receipt of data from the primary link to the backup link upon
15 detection of failure on the primary link.

 84. The method of claim 83, wherein the backup link is selected from a plurality of available links.

20 85. The method of claim 62 further comprising:
 receiving a first packet in a first protocol;
 translating the first packet into a generic format;
 passing the generic packet to an application;
 receiving from the application the generic packet;
25 translating the generic packet into a second protocol; and
 sending the translated packet to an output port.

 86. The method of claim 62 further comprising:
 receiving a connection request via an input port;
30 identifying a protocol associated with the connection request; and
 dynamically bonding the identified protocol to the input port.

 87. The method of claim 86 further comprising adding encapsulation information to the data blocks, the encapsulation information being associated with the identified protocol.

35 88. The method of claim 87 further comprising storing the encapsulation information in a cache.

1 89. In a multi-service network switch including a plurality of interface modules, a method for allocating a resource to a connection request received by one of the interface modules, the method comprising:

5 maintaining in each interface module a list of resources and information about availability of each of the resources;

 identifying a particular resource to be allocated to the connection request;

 querying the list of resources for the particular resource; and

 allocating the particular resource to the connection request if the particular resource is identified as being available.

10 90. The method of claim 89, wherein the list of resources is a list of resources local to the interface module.

 91. The method of claim 89 further comprising:

15 communicating a request for the particular resource from the receiving interface module to remaining interface modules; and

 communicating a response indicating that the particular resource is available.

 92. The method of claim 89 further comprising:

20 assigning an access level to the incoming connection request based on a characteristic of the connection request, the access level being associated with an access threshold;

 determining an amount of current usage for the particular resource; and

 allocating the identified resource to the connection request if the amount of current usage is less than the access threshold associated with the assigned access level.

25 93. The method of claim 89 further comprising:

 creating a plurality of virtual routers, each virtual router being allocated a plurality of resources;

 maintaining the list of resources according to the virtual routers;

30 identifying the virtual router associated with the connection request; and

 allocating the identified resource to the connection request if the particular resource is identified as being available for the identified virtual router.

35 94. In a multi-service network switch, a method for providing tiered access to system resources, the method comprising:

 receiving an incoming connection request;

 assigning an access level to the incoming connection request based on a characteristic of an incoming connection request, the access level being associated with an access threshold;

1 identifying the resource requested by the incoming connection request;
determining an amount of current usage for the identified resource; and
allocating the identified resource to the incoming connection request if the amount of
current usage is less than the access threshold associated with the assigned access level.

5 95. The method of claim 94, wherein the system resources are partitioned among a plurality of virtual routers.

10 96. The method of claim 94, wherein the characteristic is selected from the group consisting of a type of inlink carrying the incoming connection request, a telephone number associated with the incoming connection request, and a type of user submitting the connection request.

15 97. The method of claim 94 further comprising:
communicating a request for the identified resource, the communicated request including the identified quality of access level;
communicating a response indicating that the identified resource is available; and
communicating a request to allocate the identified resource.

20 98. In a multi-service network switch, a method for forwarding data blocks comprising:
receiving from a user a connection request;
identifying a characteristic of the connection request;
selecting a router based on the identified characteristic; and
forwarding a data block originated from the user to the selected router.

25 99. The method of claim 98, wherein the characteristic is selected from the group consisting of a type of line interface, user login information, telephone number, source address of the data block, and destination address of the data block.

30 100. The method of claim 98 further comprising retrieving call profile information based on the identified characteristic.

35 101. The method of claim 100, wherein the call profile information includes an access level to be assigned to the connection request, the access level being associated with an access threshold indicative of a maximum number of system resources that may be in use before the connection request is granted.

102. The method of claim 101 further comprising:
identifying the resource requested by the connection request;

1 determining an amount of current usage for the identified resource; and
 allocating the identified resource to the connection request if the amount of current usage
is less than the access threshold associated with the assigned access level.

5 103. The method of claim 100, wherein the call profile information includes a virtual
router identifier to be assigned to the connection request, the virtual router being allocated a
portion of the system resources.

 104. The method of claim 103 further comprising:
10 maintaining in each interface module a list of resources and information about availability
of each of the resources;
 identifying a particular resource to be allocated to the connection request;
 querying the list of resources for the particular resource; and
 allocating the particular resource to the connection request if the particular resource is
15 identified as being available.

 105. In a multi-service network switch, a method for emulating multiple routers within
the single switch, the method comprising:
 creating a plurality of virtual routers, each virtual router being associated with a unique
20 virtual router identifier;
 allocating resources to each virtual router, the allocated resources being proprietary to each
virtual router;
 creating a routing table for each virtual router;
 setting an IP interface for each virtual router; and
25 enabling each virtual router.

 106. The method of claim 105 further comprising monitoring usage of resources
allocated to each virtual router.

30 107. The method of claim 105, wherein the monitoring comprises monitoring usage of
resources allocated to each virtual router based on a quality of access level, the quality of access
level being associated with an access threshold indicative of a maximum number of resources
allowed to be in use before a resource is allocated to a connection request.

35 108. The method of claim 105 further comprising:
 receiving a connection request;
 identifying the virtual router for the connection request;
 determining a resource needed for the connection;

1 determining availability of resources allocated to the virtual router; and
 assigning the resource to the connection request if the resource is available.

5 109. The method of claim 105 further comprising creating for each virtual router a set
of filters, each filter being associated with a filtering criteria and an action to be taken upon a
match of the filtering criteria by a block of data directed to the virtual router.

 110. The method of claim 109, wherein the filtering criteria is selected from the group
consisting of a source address of the block of data and a destination address of the block of data.

10 111. The method of claim 109, wherein the action to be taken is selected from the group
consisting of forwarding the block of data and dropping the block of data.

 112. In a data switch including a plurality of interface modules, a method for providing
15 protection switching comprising:
 maintaining a backup port for each primary port coupled to the interface modules;
 receiving a block of data on the primary port;
 detecting a failure of the primary port; and
 automatically diverting the block of data from the primary port to the backup port
20 associated with the primary port upon detecting the failure.

 113. The method of claim 112, wherein the backup port resides on the same interface
module as the primary port.

25 114. The method of claim 112, wherein the backup port resides on a different interface
module as the primary port.

 115. The method of claim 112, wherein two or more primary ports are associated with
the same backup port.

30 116. In a data switch including a plurality of interface modules, a method for providing
protection switching comprising:
 maintaining a backup link for each primary link coupled to the interface modules;
 receiving a block of data on the primary link;
35 detecting a failure of the primary link; and
 automatically switching receipt of data from the primary link to the backup link upon
detection of failure on the primary link.

1 117. The method of claim 116, wherein the backup link is selected from a plurality of
available links.

5 118. In a data switch including a plurality of interface modules, a method of forwarding
a block of data comprising:

receiving a first packet in a first protocol;
translating the first packet into a generic format;
passing the generic packet to an application;
receiving from the application the generic packet;
10 translating the generic packet into a second protocol; and
sending the translated packet to an output port.

15 119. The method of claim 118 further comprising placing the generic packet into a
receiving queue corresponding to a quality of service level of the generic packet.

20 120. The method of claim 118 further comprising receiving at a forwarding queue the
generic packet from the application, the forwarding queue corresponding to a quality of service
level of the generic packet.

25 121. The method of claim 118, wherein the sending comprises sending the translated
packet to a backplane, the packet having a port address within a range reserved for a destination
port.

30 122. The method of claim 119, wherein the destination port is selected from a group
consisting of known internal unicast ports, known internal multicast ports, known external
multicast ports, and dynamic multicast ports.

35 123. A method for forwarding data blocks comprising:
receiving a connection request;
identifying a protocol associated with the connection request;
dynamically bonding the identified protocol to the input port;
receiving a data block from a layer three interface; and
adding encapsulation information to the data block, the encapsulation information being
associated with the identified protocol.

 124. The method of claim 123 further comprising storing the encapsulation information
in a cache.

1 125. A method for forwarding data blocks comprising:
 establishing a first connection on a port;
 creating a port interface (PIF) object for the port;
 detecting a first protocol of the connection;
5 bonding the first protocol to the PIF;
 receiving a data block on the port; and
 forwarding the data block to a destination address.

 126. The method of claim 125 further comprising:
10 establishing a second connection on the port;
 creating a second port interface (PIF) layer for the port;
 detecting a second protocol of the connection;
 bonding the second protocol to the second PIF;
 receiving a second data block on the port; and
15 forwarding the second data block to a second destination address.


20

25

30

35

FIG. 1








FIG. 3

FIG. 4



IP Route Table:
Total Routes: 32

Destination	Subnet Mask	NextHop	Owner	Cost
0.0.0.0	0.0.0.0	206.169.142.9	STATIC	1
0.0.0.0	0.0.0.0	206.169.114.17	STATIC	2
0.0.0.0	0.0.0.0	10.1.205.18	OSPFE	11
10.180.180.0	255.255.255.248	10.1.205.18	OSPFE	11
10.3.1.16	255.255.255.240	10.1.130.2	OSPFE	20
10.2.215.64	255.255.255.240	10.1.130.1	OSPF1	20
10.3.215.64	255.255.255.240	10.1.130.2	OSPF1	20
10.2.215.0	255.255.255.192	10.1.130.1	OSPF2	30
10.3.215.0	255.255.255.192	10.1.130.2	OSPF2	30
10.3.215.128	255.255.255.192	10.1.130.2	OSPF2	130
10.1.54.0	255.255.255.0	DIRECT	DIAL-POOL 1	
10.131.71.0	255.255.255.0	10.1.205.18	OSPFE	11
10.1.0.0	255.255.0.0	DIRECT	LOCAL	1
10.181.0.0	255.255.0.0	10.1.205.18	OSPFE	11
10.87.0.0	255.255.0.0	10.1.205.18	OSPFE	11
10.89.0.0	255.255.0.0	10.1.205.18	OSPFE	11
10.91.0.0	255.255.0.0	10.1.205.18	OSPFE	12
10.200.0.0	255.255.0.0	10.1.205.18	OSPFE	20
10.77.0.0	255.255.0.0	10.1.51.200	OSPF1	110
11.22.33.0	255.255.255.0	10.1.16.16	OSPF1	110
206.169.114.16	255.255.255.252	DIRECT	LOCAL	1
206.169.114.152	255.255.255.248	DIRECT	DIAL-POOL 1	
206.169.114.136	255.255.255.248	DIRECT	DIAL-POOL 1	

Press Enter to Continue, Any other key followed by Enter to Abort:

Fig. 5

PRI-SCM:1.1>=2:netman:ip#_view ipf

IP Forwarding Table:

Total IPF table entries: 12

92 Destination	94 Subnet Mask	96 Nexthop	98 Type	100 Flags(*)
10.3.238.1	255.255.255.255		SPORT	SD(r)
10.1.6.36	255.255.255.255		SPORT	M
10.1.6.35	255.255.255.255		SPORT	M
10.1.6.34	255.255.255.255		SPORT	M
10.1.6.33	255.255.255.255		SPORT	M
10.1.6.32	255.255.255.255		SPORT	M
10.1.6.31	255.255.255.255		SPORT	M
10.2.238.1	255.255.255.255		SPORT	SD(l)
10.1.6.30	255.255.255.255		SPORT	SD(l)
10.3.0.0	255.255.0.0		SPORT	PD(r)
10.2.0.0	255.255.0.0		SPORT	PD(l)
10.1.0.0	255.255.0.0		SPORT	PD(l)
0.0.0.0	0.0.0.0	206.169.142.9	SPORT	R

(*) D: Direct (and l = local card only, r = remote card only),
S: System i/f, R: Remote, P: Supernet, F: Default, and M: Mgmt.

Actual IPF Table Entries: 12

Fig. 6

Total IP Cache Entries: 3

Destination ¹⁰⁴	Source ¹⁰⁶	Out Port ¹⁰⁸	Header ¹¹⁰
207.200.77.45	206.169.114.138	Fr.1.5.2.3.1	08001000cca97211
206.169.114.	142 10.1.1.25	Mo.1.3.1.1.29	0800201dcca9728c
198.41.0.5	206.169.114.138	Fr.1.5.2.3.1	08000000cca97211

Fig. 7

112

IP ARP Table: 200			
202		204	206
IP Address	MAC Address	Physical Port	Type(*)
10.1.1.101	00-ff-4a-3d-2f-1a	En.1.3.1.1.1.	S
10.1.5.100	00-ff-ff-01-ff-20	En.1.3.2.1.1.	D
150.140.140.30	08-00-09-ff-65-ff	En.1.3.1.1.14	LB
147.128.128.60	08-00-09-ff-38-38	En.1.3.1.1.10	D
10.1.5.109	00-ff-ff-04-02-ff	En.1.3.2.1.8	S
(*) R: Rmt, L: Lcl, D: Dyn, S: Stat, P: Pt2Pt, T: Route and B: Bcast			
Total Arp Table Entries: 5			

Fig. 8

FIG. 9




FIG. 10

DOMAIN NAME	NEXT HOP ROUTER
ISP1	206.169.142.9
ISP2	206.169.114.17
...	...
ISPN	206.169.152.3

FIG. 11

291	SEARCH KEY	290	CALLLED-NUM.
292	SOURCE LINK		N/A
293	SOURCE CHANNEL		N/A
294	CALL TYPE:		MODEM
296	SERVICE TYPE:		PPP
298	QUALITY OF ACCESS:		1
300	QUALITY OF SERVICE:		1
302	VR ID:		1
304	VPN ID:		111
306	AUTH. SOURCE:		RADIUS
308	PRY DNS ADDR:		206.169.25.3
310	SCRY DNS ADDR:		206.169.25.100
312	PRY RADIUS SRVR:		10.1.125.26
314	SCRY RADIUS SRVR:		10.1.6.15
316	PHONE NUMBER		555-5555
311	DOMAIN ID		001



*Fig. 12*

FIG. 13

QoA LEVEL	ACCESS THRESHOLD
1	100 %
2	75 %
3	50 %
4	25 %

14/34


*Fig. 14*


334

MODEM RESOURCES						
336	VR ID					= 111
338	Max Local Resources					= 32
340	Max Global Resources					= 32
342	Current Local Resources					= 29
344	Current Global Resources					= 29
346	QOA	LOCAL QOA	GLOBAL QOA	ACCEPT LOCAL	ACCEPT GLOBAL	
		348	350	352		354
1	0	0		YES	YES	
2	8	8		YES	YES	
3	16	16		YES	YES	
4	24	24		YES	YES	

Fig. 15

FIG. 16



*Fig. 17*

240

242

IP VPN Sessions:

ID	VPN-ID	Source-Addr	Source-Mask	Dest-Addr	Dest-Mask
	244	246	248	250	252
1	111	any	any	10.1.0.0	255.255.0.0
2	any	10.1.0.0	255.255.0.0	208.227.214.0	255.255.255.0
3	any	10.1.0.0	255.255.0.0	10.1.0.0	255.255.0.0
4	any	10.1.0.0	255.255.0.0	206.169.114.128	255.255.255.192
5	any	any	any	10.1.0.0	255.255.0.0
6	any	10.1.0.0	255.255.0.0	any	any
7	any	any	any	any	any

Fig. 18

254

256

PRI-SCM:1.2>=14:netman:ip#						
IP VPN Rules:						
ID	Pri	Action	IP-Proto	App-Proto	SessCnt	Pkt Count
---	---	---	---	---	---	---
1	1	Fwd	tcp	ftp	5	3939981
2	1	Drop	all	-	2	3
PRI-SCM:1.2>=14:netman:ip#						


Fig. 19


270


PRI-SCM:1.1>=3:netman:ip# view ppn-filter																			
IP VPN List of rules attached to sessions:																			
272	<table><tr><th>SessID</th><th>Rule List (In order of priority)</th></tr><tr><td colspan="2">-----</td></tr><tr><td>1</td><td>1 274</td></tr><tr><td>2</td><td>1</td></tr><tr><td>3</td><td>1</td></tr><tr><td>4</td><td>1</td></tr><tr><td>5</td><td>2</td></tr><tr><td>6</td><td>2</td></tr><tr><td>7</td><td>1</td></tr></table>	SessID	Rule List (In order of priority)	-----		1	1 274	2	1	3	1	4	1	5	2	6	2	7	1
SessID	Rule List (In order of priority)																		


1	1 274																		
2	1																		
3	1																		
4	1																		
5	2																		
6	2																		
7	1																		
PRI-SCM:1.1>=4:netman:ip#																			


Fig. 20


FIG. 21



*Fig. 22*

*Fig. 23*

*Fig. 24*

*Fig. 25*

*Fig. 26*

*Fig. 27*




Fig 30

FPA

	CHASS	SLOT	PM	CONT	PORT NUM
--	-------	------	----	------	----------

Fig 31

PPA

	CHASS	SLOT	PM	LINK	CHAN NUM
--	-------	------	----	------	----------


Fig 32

INPUT PORT FORMAT

28 27				24 23 22 21				18 17		12 11	
LA	3	S	S	PORT TYPE	CHASS	CARD	CONTROLLER	PORT			
NT	P	P	P								
TYPE	ARE	ARE	ARE								

31/34

OUTPUT PORT FORMAT



↑
714

Fig 34

Port Addr Range	Type	Chass	Card	Control
0-19	Well Known Internal Multicast Address	NA	NA	0
20-38	Well Known Internal Unicast Address	NA	Card Num	0
40-79	Well Known External Multicast Address	NA	NA	0
80-111	Dynamic External Multicast Address	NA	NA	0
112-2048	Reserved Port Address	Chass Num	Card Num	0

Fig. 35




Fig 36

34/34




Fig 29

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 August 2000 (31.08.2000)


PCT

(10) International Publication Number
WO 00/51290 A3

- (51) International Patent Classification⁷: H04L 12/44, 60/121,591 23 February 1999 (23.02.1999) US
12/46, 12/56, 29/14 60/121,592 23 February 1999 (23.02.1999) US
60/121,593 23 February 1999 (23.02.1999) US
- (21) International Application Number: PCT/US00/04717
- (22) International Filing Date: 23 February 2000 (23.02.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/121,270 23 February 1999 (23.02.1999) US
60/121,271 23 February 1999 (23.02.1999) US
60/121,272 23 February 1999 (23.02.1999) US
60/121,273 23 February 1999 (23.02.1999) US
60/121,274 23 February 1999 (23.02.1999) US
60/121,275 23 February 1999 (23.02.1999) US
60/121,276 23 February 1999 (23.02.1999) US
60/121,277 23 February 1999 (23.02.1999) US
60/121,278 23 February 1999 (23.02.1999) US
60/121,279 23 February 1999 (23.02.1999) US
60/121,589 23 February 1999 (23.02.1999) US
60/121,590 23 February 1999 (23.02.1999) US
- (71) Applicant: ALCATEL INTERNETWORKING, INC.
[US/US]; 26801 West Agoura Road, Calabasas, CA 91301 (US).
- (72) Inventors: RAO, Ramakrishna; 916 Pramukh's Way, San Jose, CA 95120 (US). GHAREMANI, Charlie; 6566 Deer Hollow Drive, San Jose, CA 95120 (US). YOUNG, Desmond; 23050 Old Logging Road, Los Gatos Mountains, CA 95033 (US). MURTHY, Manohar; 1969 Vinehill Circle, Fremont, CA 94539 (US). TSENG, Ben; 4121 Wilkie Court, Palo Alto, CA 94306 (US). NAGARAJ, Ashwath; 25769 Elena Road, Los Altos, CA 94022 (US). FARID, Mehdi; 22540 Hutchinson Road, Los Gatos, CA 95033 (US). SCHUNK, Richard; 64 King Street, Norfolk, MA 02056 (US).
- (74) Agent: CHANG, Josephine, E.; Christie, Parker & Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).
- (81) Designated States (national): AU, CN, JP.

[Continued on next page]

(54) Title: MULTI-SERVICE NETWORK SWITCH



(57) Abstract: A multi-service network switch capable of providing multiple network services from a single platform. The switch incorporates a distributed packet forwarding architecture where each of the various cards is capable of making independent forwarding decisions. The switch further allows for dynamic resource management for dynamically assigning modem and ISDN resources to an incoming call. The switch may also include fault management features to guard against single points of failure within the switch. The switch further allows the partitioning of the switch into multiple virtual routers where each virtual router has its own set of resources and a routing table. Each virtual router is further partitioned into virtual private networks for further controlling access to the network. The switch's supports policy based routing where specific routing paths are selected based a domain name, a telephone number, and the like. The switch also provides tiered access of the Internet by defining quality of access levels to each incoming connection request. The switch may further support an IP routing protocol and architecture in which the layer two protocols are independent of the physical interface they run on. Furthermore, the switch includes a generic forwarding interface software for hiding the details of transmitting and receiving packets over different interface types.

WO 00/51290 A3



(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(88) Date of publication of the international search report:
5 April 2001

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

Int'l Application No

PCT/US 00/04717

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/46 H04L12/56 H04L29/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 00945 A (SUN MICROSYSTEMS INC) 7 January 1999 (1999-01-07) page 17, line 5 -page 20, line 16 page 24, line 12 -page 25, line 18 page 27, line 19 -page 28, line 21 figures 2,3	1,3,4, 62,64,65
Y	---	2,63
Y	US 5 740 175 A (MYERS JR ROY T ET AL) 14 April 1998 (1998-04-14) abstract	2,63
A	---	1,3,4, 62,64,65
A	WO 99 07078 A (CUBE INC I) 11 February 1999 (1999-02-11) abstract	1-4, 62-65

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 October 2000

Date of mailing of the international search report

19. 01. 01

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Eraso Helguera, J

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 00/04717

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.

2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.

3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-4, 62-65

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

1. Claims: 1-4, 62-65

A multi-service network switch and a method for performing dynamic address resolution in a network switch.

2. Claims: 5-9 (as dependant on 1), 32-42,
66-70 (as dependant on 62), 94-104

A multi-service network switch and a method for providing policy based routing and quality of service management in a network switch.

3. Claims: 10-14 (as dependant on 1), 27-31,
71-75 (as dependant on 62), 89-93

A multi-service network switch and a method for providing a list of resources and availability of each of them in a network switch.

4. Claims: 15-17 (as dependant on 1), 43-45,
76-78 (as dependant on 62), 105-111

A data switch and a method for providing multiple virtual routers in a network switch.

5. Claims: 18-22 (as dependant on 1), 46-51,
79-84 (as dependant on 62), 112-117

A data switch and a method for providing automatic protection switching in a network switch.

6. Claims: 23 (as dependant on 1), 52-57,
85 (as dependant on 62), 118-122

A data switch and a method for using a generic packet format inside a network switch.

7. Claims: 24-26 (as dependant on 1), 58-61,
86-88 (as dependant on 62), 123-126

A data switch and a method for dynamically bonding a protocol to an input port in a network switch.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/US 00/04717

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9900945	A	07-01-1999	US 6115378 A EP 1002401 A	05-09-2000 24-05-2000
US 5740175	A	14-04-1998	NONE	
WO 9907078	A	11-02-1999	US 5940596 A	17-08-1999